

ALLOY C276

MSDS Number

BBTXY

National Stock Number

9535-00F006112

Product Name

ALLOY C276

Manufacturer

G AND S TITANIUM INC

Product Identification

Product ID:ALLOY C276
MSDS Date:01/01/1987
FSC:9535
NIIN:00F006112
MSDS Number: BBTXY

Responsible Party

G & S TITANIUM, INC/WOOSTER, OH 44691
Emergency Phone: (216) 263-0564
Cage: FO168

Contractor

G & S TITANIUM, INC/WOOSTER, OH 44691
WOOSTER, OH 44691
(216) 263-0564
Cage: FO168

Ingredients

CHROMIUM (SARA III)
CAS: 7440-47-3
RTECS: GB4200000
Fraction By Weight: 16%
OSHA PEL1 MG/M3
ACGIH TLV: 0.5 MG/M3; 9192
EPA Report Quantity: 1 LB
DOT Report Quantity: 1 LB

IRON OXIDE

CAS: 1309-37-1
RTECS: NO7400000
Fraction By Weight: 7%
OSHA PEL10 MG/M3 (FE)
ACGIH TLV: 5 MG/M3(FE),B2; 9293

MOLYBDENUM

CAS: 7439-98-7

RTECS: QA4680000

Fraction By Weight: 16%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3; 9293

NICKEL (SARA III)

CAS: 7440-02-0

RTECS: QR5950000

Fraction By Weight: 57%

OSHA PEL1 MG/M3

ACGIH TLV: 1 MG/M3; 9192

TUNGSTEN

CAS: 7440-33-7

RTECS: YO7175000

Fraction By Weight: 4%

OSHA PEL5 MG/M3/ 10 STEL

ACGIH TLV: 5 MG/M3/10 STEL;9192

Hazards

Effects of Overexposure:NAUSEA; TIGHTNESS OF CHEST; FEVER; EYES, NOSE, THROAT, OR SKIN IRRIT; LOSS OF CONSCIOUSNESS/DEATH.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. IF VICTIM IS UNCONSCIOUS, ADMINISTER OXYGEN. SKIN: BRUSH OFF SKIN & CLOTHING. WASH W/SOAP & WATER. WOUNDS: REMOVE METALLIC PARTICLES/CLEANSE. INGESTION: SEEK MED ATT. EYES: FLUSH W/WATER. SEEK MED ATT.

Fire Fighting

Flash Point:NONFLAMMABLE

Extinguishing Media:SAND, DOLOMITE, GRAPHITE POWDER, OR SODIUM CHLORIDE.

Unusual Fire/Explosion Hazard:MODERATE FIRE & EXPLOSIVE HAZARD WHEN EXPOSED TO HEAT, FLAME, ELECTRIC CURRENT, OR SPARK.

Accidental Release

Spill Release Procedures:RESIDUE FROM CUTTING OR GRINDING SHOULD BE SWEEPED OR VACUUMED & PLACED IN SUITABLE COAINERS.

Handling

Handling and Storage Precautions:PREVENT ACCUMULATION OF DUST, GRINDINGS, ETC. THROUGH THE USE OF GOOD HOUSEKEEPING PRACTICES.

Exposure Controls

Respiratory Protection:IF TLVS ARE EXCEEDED, USE OSHA APPROVED RESPIRATOR.

Ventilation:PROVIDE EXHAUST VENTILATION TO KEEP Eye Protection:GOGGLES

Other Protective Equipment:TO BE USED WHEN CUTTING, GRINDING, OR WELDING.

Supplemental Safety and Health

MSDS UNDATED

Chemical Properties

Solubility in Water:NOT SOLUBLE

Appearance and Odor:STEEL GRAY IN COLOR.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, NITRIC OF CHROMIC ACIDS.

Disposal

Waste Disposal Methods:DISPOSAL BY LOCAL, STATE, OR FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.