

XRF-15 FIXER & REPLENISHER-WORKING STRENGT

MSDS Number

BBVFJ

National Stock Number

6750-00F006220

Product Name

XRF-15 FIXER & REPLENISHER-WORKING STRENGT

Manufacturer

ALLIED PHOTO PRODUCTS CO

Product Identification

Product ID:XRF-15 FIXER & REPLENISHER-WORKING STRENGT

MSDS Date:01/01/1987

FSC:6750

NIIN:00F006220

MSDS Number: BBVFJ

Responsible Party

ALLIED PHOTO PRODUCTS CO/NORCROSS, GA 30093

Emergency Phone: (404) 448-0250

Cage: 1CG79

Contractor

ALLIED PHOTO PRODUCT CO,SUB OF ALLIED PRODUCT CORP

NORCROSS, GA 30093-2251

US

770-448-0250

Cage: 1CG79

Ingredients

AMMONIUM THIOSULFATE

CAS: 7783-18-8

RTECS: XN6465000

Fraction By Weight: 9-12%

ACETIC ACID

RTECS: AF1340000

Fraction By Weight: 1-2%

ACGIH TLV: 10 PPMG

ALUMINUM SULFATE (SARA III)

CAS: 10043-01-3

RTECS: BD1700000

Fraction By Weight: 1-2%

OSHA PEL2 MG/M3

ACGIH TLV: 2 MG/M3; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

First Aid

First Aid:EYES: FLUSH W/WATER FOR AT LEAST 15 MINUTES & GET MEDICAL ATTENTION. SKIN: FLUSH W/PLENTY OF WATER. IF SKIN IRRITATION DEVELOPS, GET MEDICAL ATTENTION. INGESTION: SEEK IMMEDIATE MEDICAL ADVICE GIVING FULL DETAILS OF AMT SWALLOWED & TOXICITY.

Fire Fighting

Flash Point:NON COMBUSTIBLE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:USE THE MEDIA SUGGESTED TO EXTINGUISH THE SOURCE OF THE FIRE
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:WEAR PROTECTIVE CLOTHING. IF FEDERAL, STATE & LOCAL REGULATIONS PERMIT/FLUSH TO SEWEE/LARGE AMTS OF WATER. OTHERWISE ADD DRY ABSORBENT, CLEAN UP & PLACE IN APPROVED D.O.T. CONTAINER, LABEL & SEAL FOR DISPOSAL.

Handling

Handling and Storage Precautions:KEEP TIGHTLY SEALED. DON'T STORE OR CONSUME FOOD, DRINK OR TOBACCO IN AREA WHERE THEY MAY BECO CONTAMINATED WITH THIS MATERIAL. STORE >40F.
Other Precautions:AVOID UNNECESSARY PERSONAL CONTACT. AVOID INCOMPATIBLE SUBSTANCES. WASH THOROUGHLY AFTER HANDLING.

Exposure Controls

Respiratory Protection:NONE SHOULD BE NEEDED
Ventilation:GOOD VENTILATION REQUIRED
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES/GOGGLES
Other Protective Equipment:AS NECESSARY TO PREVENT EYE & SKIN CONTACT.
Supplemental Safety and Health
MSDS DATE: 3/17/86. PH: 4.25

Chemical Properties

Boiling Pt:B.P. Text:>212F
Vapor Pres:16
Vapor Density:0.6
Spec Gravity:1.08
Solubility in Water:COMPLETE
Appearance and Odor:COLORLESS LIQUID W/SLIGHT ACETIC ACID ODOR.
Percent Volatiles by Volume:95%

Stability

Stability Indicator/Materials to Avoid:YES
STRONG ALKALIES

Disposal

Waste Disposal Methods:IF FEDERAL, STATE & LOCAL REGULATIONS PERMIT, FLUSH TO SEWER W/LARGE AMTS OF WATER. OTHERWISE DISPOSE OF CONTAMINATED PRODUCT & MATERIALS USED IN CLEANING UP SPILLS IN A MANNER APPROVED FOR THIS MATER IAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

