

## **CLASSIC 99 SEMI-GLOSS ALKYD ENL A40 W7 BASE**

### **MSDS Number**

BBVKS

### **National Stock Number**

8010-00F006310

### **Product Name**

CLASSIC 99 SEMI-GLOSS ALKYD ENL A40 W7 BASE

### **Manufacturer**

SHERWIN WILLIAMS CO

### **Product Identification**

Product ID:CLASSIC 99 SEMI-GLOSS ALKYD ENL A40 W7 BASE

MSDS Date:01/01/1987

FSC:8010

NIIN:00F006310

MSDS Number: BBVKS

### **Responsible Party**

SHERWIN-WILLIAMS CO/CLEVELAND, OH 44115

Emergency Phone: (216) 566-2917

Cage: 54636

### **Contractor**

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

### **Ingredients**

MINERAL SPIRITS 140-FLASH. (35-40%) (VAPOR PRESSURE = 0.5)

Fraction By Weight: 40%

ACGIH TLV: 100 PPM

### **Hazards**

Effects of Overexposure:ANESTHETIC/LIGHTHEADEDNESS/STAGGERING GAIT/SKIN IRRITANT/UPPER RESPIRATORY SYSTEM/NERVOUS DAMAGE.

### **First Aid**

First Aid:INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING & LAUNDRER BEFORE RE-USE. EYES: FLU SH W/WATER FOR 15 MINS. GET MEDICAL ATTENTION.

### **Fire Fighting**

Flash Point:105F PMCC

Lower Limits:0.9%

Extinguishing Media:CO2, DRY CHEMICAL, FOAM

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT INCLUDING SCBA SHOULD BE USED.

Unusual Fire/Explosion Hazard:WATER COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP/AUTOIGNITION/EXPLOSION WHEN EXPOSED TO HEAT.

### **Accidental Release**

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE &

REMOVE WITH INERT ABSORBENT.

## Handling

Handling and Storage Precautions:USE ONLY WITH ADEQUATE VENTILATION.  
AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & ES. WASH  
HANDS AFTER USING.

Other Precautions:PROTECT AGAINST DUST WHICH MAY BE GENERATED BY  
SANDING OR ABRADING THE DRIED FILM.

## Exposure Controls

Respiratory Protection:WEAR RESPIRATORY DEVICE APPROVED BY NIOSH/MSHA  
IF >TLV.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:RECOMMENDED

Eye Protection:WEAR SAFETY SPECTACLES

Supplemental Safety and Health

MSDS DATE: 3/20/86. WT/GAL: 9.0-10.6

## Chemical Properties

Boiling Pt:B.P. Text:355-416F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:61%

## Stability

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO<sub>2</sub>, CO

## Disposal

Waste Disposal Methods:WASTE MUST BE TESTED FOR IGNITABILITY TO  
DETERMINE THE APPLICABLE EPA HAZARDOUS WASTE NUMBERS. INCINERATE IN  
APPROVED FACILITY. DON'T INCINERATE CLOSED CONTAINER. DISPOSE OF IN  
ACCORDANCE WITH FEDERAL , STATE & LOCAL REGULATIONS REGARDING  
POLLUTION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.