

ACRYLIC LTX FLOOR ENL, A24 G 12 EVERGREEN

MSDS Number

BBVMM

National Stock Number

8010-00F006342

Product Name

ACRYLIC LTX FLOOR ENL, A24 G 12 EVERGREEN

Manufacturer

SHERWIN WILLIAMS CO

Product Identification

Product ID: ACRYLIC LTX FLOOR ENL, A24 G 12 EVERGREEN

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00F006342

MSDS Number: BBVMM

Responsible Party

SHERWIN-WILLIAMS CO/CLEVELAND, OH 44115

Emergency Phone: (216) 566-2902

Cage: 54636

Contractor

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

Ingredients

2-(2-BUTOXYETHOXY)-ETHANOL (VAPOR PRESSURE = 0.1)

CAS: 112-34-5

RTECS: KJ9100000

Fraction By Weight:

ACGIH TLV: 50 PPM

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM, VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

CHROMIUM ION (CR 3+)

CAS: 16065-83-1

RTECS: GB6261000

Fraction By Weight: 2.8%

OSHA PEL0.5 MG/M3 (CR)

ACGIH TLV: 0.5 MG/M3 (CR); 8990

CHROMIUM (III) OXIDE

CAS: 1308-38-9

RTECS: GB6475000

Fraction By Weight: 0-5%

OSHA PEL0.5 MG/M3 (CR)

ACGIH TLV: 0.5 MG/M3 (CR); 8990

Hazards

Effects of Overexposure:LIGHTHEADEDNESS/STAGGERING GAIT/IRRITANT TO SKIN & UPPER RESPIRATORY SYSTEM.

First Aid

First Aid:INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING/LAUNDRER BEFORE RE-USE. EYES: FLUSH W/WATER FOR 15 MINS. GET MEDICAL ATTENTION.

Fire Fighting

Flash Point:>199F PMCC

Extinguishing Media:CO2, DRY CHEMICAL, ALCOHOL FOAM

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT INCLUDING SCBA SHOULD BE USED.

Unusual Fire/Explosion Hazard:WATER COOL CLOSED CONTAINERS TO PREV. PRESSURE BUILD-UP/AUTOIGNITION/EXPLOSION WHEN EXPOSED TO HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE & REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. DON'T TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDRE USE ONLY WITH ADEQUATE VENTILATION.

Other Precautions:AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EYES. WASH HANDS AFTER USING. PROTECT AGAINST DUST WHICH MAY BE GERATED BY SANDING OR ABRADING THE DRIED FILM.

Exposure Controls

Respiratory Protection:WEAR RESPIRATORY DEVICE APPROVED BY NIOSH/MSHA FOR PROTECTION.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:RECOMMENDED

Eye Protection:WEAR SAFETY SPECTACLES

Supplemental Safety and Health

MSDS DATE: 03/19/86. PH: 8.9. WT/GAL: 9.6

Chemical Properties

Boiling Pt:B.P. Text:212-448F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:70%

Stability

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO2, CO

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DON'T INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.