

B75 W C75 ANTIQUE WHITE

MSDS Number

BBVNV

National Stock Number

8010-00F006369

Product Name

B75 W C75 ANTIQUE WHITE

Manufacturer

SHERWIN WILLIAMS CO

Product Identification

Product ID: B75 W C75 ANTIQUE WHITE

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00F006369

MSDS Number: BBVNV

Responsible Party

SHERWIN-WILLIAMS CO/CLEVELAND, OH 44115

Emergency Phone: (216) 566-2917

Cage: 54636

Contractor

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

Ingredients

2-(2-BUTOXYETHOXY)-ETHANOL (VAPOR PRESSURE = 0.1)

CAS: 112-34-5

RTECS: KJ9100000

Fraction By Weight:

ACGIH TLV: 50 PPM

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

Hazards

Effects of Overexposure: ANESTHETIC, LIGHTHEADEDNESS, STAGGERING GAIT, IRRITANT TO SKIN & UPPER RESPIRATORY SYSTEM.

First Aid

First Aid:INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING/LAUNDER BEFORE RE-USE. EYES: FLUSH W/WATER FOR 15 MINS. GET MEDICAL ATTENTION.

Fire Fighting

Flash Point:>199F PMCC
Extinguishing Media:CO2, DRY CHEMICAL, ALCOHOL FOAM
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT/SCBA. WATER COOL CONTAINERS.
Unusual Fire/Explosion Hazard:WATER COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP/AUTOIGNITION/EXPLOSION WHEN EXPOSED TO HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE & REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions:USE ONLY W/ADEQUATE VENTILATION. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EY. WASH HANDS AFTER USING. DON'T TAKE INTERNALLY.
Other Precautions:PROTECT AGAINST DUST WHICH MAY BE GENERATED BY SANDIING OR ABRADING THE DRIED FILM. KEEP CONTAINER CLOSED WHEN NOT IN USE. KP OUT OF THE REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:WEAR RESPIRATORY DEVICE APPROVED BY NIOSH/MSHA FOR PROTECTION.
Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP
Protective Gloves:RECOMMENDED
Eye Protection:WEAR SAFETY SPECTACLES
Supplemental Safety and Health
MSDS DATE: 03/25/86. PH: 9-9.5%. WT/GAL: 10.1-11.5.

Chemical Properties

Boiling Pt:B.P. Text:212-448F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:75%

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CO2, CO

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.