

## **Y24 W 516 EXTERIOR WOOD UNDERCOATER, WHITE**

### **MSDS Number**

BBVPW

### **National Stock Number**

8010-00F006391

### **Product Name**

Y24 W 516 EXTERIOR WOOD UNDERCOATER, WHITE

### **Manufacturer**

SHERWIN WILLIAMS CO

### **Product Identification**

Product ID:Y24 W 516 EXTERIOR WOOD UNDERCOATER, WHITE

MSDS Date:01/01/1987

FSC:8010

NIIN:00F006391

MSDS Number: BBVPW

### **Responsible Party**

SHERWIN-WILLIAMS CO/CLEVELAND, OH 44115

Emergency Phone: (216) 566-2917

Cage: 54636

### **Contractor**

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

### **Ingredients**

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 10%

OSHA PEL100 PPM

MINERAL SPIRITS 140-FLASH (VAPOR PRESSURE = 0.5)

Fraction By Weight: 20%

ACGIH TLV: 100 PPM

### **Hazards**

Effects of Overexposure:ANESTHETIC, LIGHTHEADEDNESS, STAGGERING GAIT,  
IRRITANT TO SKIN & UPPER RESPIRATORY SYSTEM.

### **First Aid**

First Aid:INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE  
BREATHING. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY  
W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING/LAUNDER BEFORE RE-USE.  
EYES: FLUSH W/WATER FOR 15 MINS. GET MEDICAL ATTENTION.

### **Fire Fighting**

Flash Point:>115F PMCC  
Lower Limits:0.9%  
Extinguishing Media:CO2, DRY CHEMICAL, FOAM  
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT SCBA. WATER FOG COOL CONTAINERS.  
Unusual Fire/Explosion Hazard:WATER COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP/AUTOIGNITION/EXPLOSION WHEN EXPOSED TO HEAT

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE & REMOVE WITH INERT ABSORBENT.

## Handling

Handling and Storage Precautions:USE ONLY W/ADEQUATE VENTILATION. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EY. WASH HANDS AFTER USING. DO NOT TAKE INTERNALLY.  
Other Precautions:PROTECT AGAINST DUST WHICH MAY BE GENERATED BY SANDING OR ABRADING THE DRIED FILM. KEEP CONTAINER CLOSED WHEN NOT IN USE. KE OUT OF REACH OF CHILDREN. KEEP AWAY FROM HEAT/SPARKS/FLAME.

## Exposure Controls

Respiratory Protection:WEAR RESPIRATORY DEVICE APPROVED BY NIOSH/MSHA AS NEEDED  
Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:RECOMMENDED  
Eye Protection:WEAR SAFETY SPECTACLES  
Supplemental Safety and Health  
MSDS DATE: 05/24/86. WT/GAL: 11. COATING CONTAINS MATERIALS CLASSIFIED AS NUISANCE PARTICULATES (TITANIUM DIOXIDE, CALCIUMARBONATE).

## Chemical Properties

Boiling Pt:B.P. Text:300-416F  
Vapor Density:>AIR  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:45%

## Stability

Stability Indicator/Materials to Avoid:YES  
Hazardous Decomposition Products:CO2, CO

## Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.