

Y24 W 38 EXTERIOR WOOD UNDERCOATER, WHITE

MSDS Number

BBVPX

National Stock Number

8010-00F006392

Product Name

Y24 W 38 EXTERIOR WOOD UNDERCOATER, WHITE

Manufacturer

SHERWIN WILLIAMS CO

Product Identification

Product ID:Y24 W 38 EXTERIOR WOOD UNDERCOATER, WHITE

MSDS Date:01/01/1987

FSC:8010

NIIN:00F006392

MSDS Number: BBVPX

Responsible Party

SHERWIN-WILLIAMS CO/CLEVELAND, OH 44115

Emergency Phone: (216) 566-2917

Cage: 54636

Contractor

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 10%

OSHA PEL100 PPM

MINERAL SPIRITS 140-FLASH (VAPOR PRESSURE = 0.5)

Fraction By Weight: 20%

ACGIH TLV: 100 PPM

Hazards

Effects of Overexposure:ANESTHETIC, LIGHTHEADEDNESS, STAGGERING GAIT, IRRITANT TO SKIN & UPPER RESPIRATORY SYSTEM.

First Aid

First Aid:INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING/LAUNDER BEFORE RE-USE. EYES: FLUSH W/WATER FOR 15 MINS. GET MEDICAL ATTENTION.

Fire Fighting

Flash Point:>115F PMCC
Lower Limits:0.9%
Extinguishing Media:CO2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT SCBA. WATER FOG COOL CONTAINERS.
Unusual Fire/Explosion Hazard:WATER COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP/AUTOIGNITION/EXPLOSION WHEN EXPOSED TO HEAT

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE & REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions:USE ONLY W/ADEQUATE VENTILATION. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EY. WASH HANDS AFTER USING. DO NOT TAKE INTERNALLY.
Other Precautions:PROTECT AGAINST DUST WHICH MAY BE GENERATED BY SANDING OR ABRADING THE DRIED FILM. KEEP CONTAINER CLOSED WHEN NOT IN USE. KE OUT OF REACH OF CHILDREN. KEEP AWAY FROM HEAT/SPARKS/FLAME.

Exposure Controls

Respiratory Protection:WEAR RESPIRATORY DEVICE APPROVED BY NIOSH/MSHA AS NEEDED
Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:RECOMMENDED
Eye Protection:WEAR SAFETY SPECTACLES
Supplemental Safety and Health
MSDS DATE: 05/24/86. WT/GAL: 11. COATING CONTAINS MATERIALS CLASSIFIED AS NUISANCE PARTICULATES (TITANIUM DIOXIDE, CALCIUMARBONATE).

Chemical Properties

Boiling Pt:B.P. Text:300-416F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:45%

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CO2, CO

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.