

B32 W 101, PROMAR, PURE WHITE

MSDS Number

BBVQL

National Stock Number

8010-00F006403

Product Name

B32 W 101, PROMAR, PURE WHITE

Manufacturer

SHERWIN WILLIAMS CO

Product Identification

Product ID: B32 W 101, PROMAR, PURE WHITE

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00F006403

MSDS Number: BBVQL

Responsible Party

SHERWIN-WILLIAMS CO/CLEVELAND, OH 44115

Emergency Phone: (216) 566-2917

Cage: 54636

Contractor

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

Ingredients

MINERAL SPIRITS 140-FLASH (VAPOR PRESSURE = 0.5)

Fraction By Weight: 25%

ACGIH TLV: 100 PPM

SILICA, CRYSTALLINE - CRISTOBALITE

CAS: 14464-46-1

RTECS: VV7325000

Fraction By Weight: 1.97%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.05 MG/M3 RDUST9293

Hazards

Effects of Overexposure: ANESTHETIC/LIGHTHEADEDNESS/STAGGERING
GAIT/IRRITANT TO SKIN & UPPER RESPIRATORY/BRAIN DAMAGE.

First Aid

First Aid: INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE
BREATHING. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY
W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING/LAUNDRER BEFORE RE-USE.
EYES: FLUSH W/WATER FOR 15 MINS. GET MEDICAL ATTENTION.

Fire Fighting

Flash Point:105F PMCC
Lower Limits:0.9%
Extinguishing Media:CO2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT SCBA. WATER FOG COOL CONTAINERS.
Unusual Fire/Explosion Hazard:WATER COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP/AUTOIGNITION/EXPLOSION WHEN EXPOSED TO HEAT

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions:USE ONLY W/ADEQUATE VENTILATION. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EY. WASH HANDS AFTER USING. DO NOT TAKE INTERNALLY.
Other Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP AWAY FROM HEAT/FLAME. PROTECT AGAINST DUST WHICH MAY BE GENERATED BY SANDING OR RADING THE DRIED FILM. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:WEAR RESPIRATORY DEVICE APPROVED BY NIOSH/MSHA AS NEEDED.
Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:RECOMMENDED
Eye Protection:WEAR SAFETY SPECTACLES
Supplemental Safety and Health
MSDS DATE: 04/5/86. WT/GAL: 12.75. COATING CONTAINS MATERIALS CLASSIFIED AS NUISANCE PARTICULATES (TITANIUM DIOXIDE, CALCI CARBONATE).

Chemical Properties

Boiling Pt:B.P. Text:355-416F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:51.4

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES, HOT SURFACES
Hazardous Decomposition Products:CO2, CO

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.