

B31 W 402 MIDTONE (BASE Y) PROMAR

MSDS Number

BBVRH

National Stock Number

8010-00F006426

Product Name

B31 W 402 MIDTONE (BASE Y) PROMAR

Manufacturer

SHERWIN WILLIAMS CO

Product Identification

Product ID:B31 W 402 MIDTONE (BASE Y) PROMAR MSDS Date: 01/01/1987 FSC:8010 NIIN:00F006426

MSDS Number: BBVRH

Responsible Party

SHERWIN-WILLIAMS CO/CLEVELAND, OH 44115

Emergency Phone: (216) 556-2917

Cage: 54636 **Contractor**

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

Ingredients

2-(2-BUTOXYETHOXY)-ETHANOL (VAPOR PRESSURE = 0.1)

CAS: 112-34-5 RTECS: KJ9100000 Fraction By Weight: ACGIH TLV: 50 PPM

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000 Fraction By Weight: OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM, VAPOR; 9192

EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

Hazards

Effects of Overexposure: ANESTHETIC, LIGHTHEADEDNESS, STAGGERING GAIT, IRRITANT TO SKIN & UPPER RESPIRATORY SYSTEM.



First Aid

First Aid:INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING/LAUNDER BEFORE RE-USE. EYES: FLUSH WITH WATER FOR 15 MINS. GET MEDICAL ATTENTION

Fire Fighting

Flash Point:>199F PMCC
Extinguishing Media:CO2, DRY CHEMICAL, ALCOHOL FOAM
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT SCBA. WATER FOG COOL
CONTAINERS.
Unusual Fire/Explosion Hazard:WATER COOL CLOSED CONTAINERS TO PREVENT

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

PRESSURE BUILDUP/AUTOIGNITION/EXPLOSION WHEN EXPOSED TO HEAT

Handling

Handling and Storage Precautions: USE ONLY W/ADEQUATE VENTILATION. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EY. WASH HANDS AFTER USING. DO NOT TAKE INTERNALLY.

Other Precautions: PROTECT AGAINST DUST WHICH MAY BE GENERATED BY SANDING OR ABRADING THE DRIED FILM. KEEP CONTAINER CLOSED WHEN NOT IN USE. KE OUT OF REACH OF CHILDREN.

Respiratory Protection: WEAR RESPIRATORY DEVICE APPROVED BY NIOSH/MSHA

Exposure Controls

AS NEEDED

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:RECOMMENDED Eye Protection:WEAR SAFETY SPECTACLES

Supplemental Safety and Health

MSDS DATE: 03/25/86. WT/GAL: 9.2-10.2. PH: 8.6. COATING CONTAINS

MATERIALS CLASSIFIED AS NUISANCE PARTICULATES (TITANIUM DXIDE, CALCIUM CARBONATE).

Chemical Properties

Boiling Pt:B.P. Text:212-448F Vapor Density:>AIR Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume: 70%

Stability

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:CO2, CO

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.