

A6 N56 PLANTATION BROWN FLAT LTX HOUSE

MSDS Number

BBXJK

National Stock Number

8010-00F007160

Product Name

A6 N56 PLANTATION BROWN FLAT LTX HOUSE

Manufacturer

SHERWIN WILLIAMS COMPANY

Product Identification

Product ID:A6 N56 PLANTATION BROWN FLAT LTX HOUSE

MSDS Date:04/10/1985

FSC:8010

NIIN:00F007160

MSDS Number: BBXJK

Responsible Party

SHERWIN-WILLIAMS COMPANY

101 PROSPECT AVENUE N.W.

CLEVELAND , OH 44115

Emergency Phone: (216) 556-2917

Info Phone: (216) 556-2909

Cage: 54636

Contractor

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

Ingredients

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 0-5%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

ANTIMONY (SARA III)

CAS: 7440-36-0

RTECS: CC4025000

Fraction By Weight: 0-1%

OSHA PEL0.5 MG/M3

ACGIH TLV: 0.5 MG SB/M3; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: IN A CONFINED AREA VAPORS
IN HIGH CONCENTRATION ARE ANESTHETIC. MAY RESULT IN
LIGHTHEADEDNESS, STAGGERING GAIT, & IRRITATION TO THE UPPER
RESPIRATORY SYSTEM. SKIN: IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: IN A CONFINED AREA VAPORS IN HIGH
CONCENTRATION ARE ANESTHETIC. MAY RESULT IN LIGHTHEADEDNESS,
STAGGERING GAIT, & IRRITATION TO THE UPPER RESPIRATORY SYSTEM.
SKIN: IRRITATION.

First Aid

First Aid:INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE
BREATHING. KEEP WARM/QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY
W/SOAP & WATER. REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
EYES: FLUSH W/ LARGE AMOUNTS OF WATER FOR 15 MINTUES. GET MEDICAL
ATTENTION. INGESTION: GET MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:PMCC
Flash Point:>199F
Extinguishing Media:CO2, DRY CHEMICAL, ALCOHOL FOAM
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT/SCBA. WATER SPRAY
MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:WATER MAY BE USED TO COOL CLOSED
CONTAINERS TO PREVENT PRESSURE BUILD-UP & POSSIBLE AUTOIGNITION OR
EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE &
REMOVE W/INERT ABSORBENT.

Handling

Handling and Storage Precautions:KEEP CONTIANER CLOSED WHEN NOT IN USE.
DON'T TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. TRANSFER
ONLY TO APPROVED CONTAINERS W/LABELING.
Other Precautions:PROTECT AGAINST HAZARDOUS DUST OR FUMES WHICH MAY BE
GENERATED BY SANDING, ABRADING, BURNING, BRASING OR WELDING DRIED
FILM. USE ONLY W/ADEQUATE VENTILATION. AVOID BREATHING VAPOR/SPRAY
MIST & CONTACT W/SKIN & EYES. WASH HANDS AFTER USING.

Exposure Controls

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BY VENTILATION, WEAR RESPIRATORY DEVICE APPROVED BY NIOSH MS
PROTECTION AGAINST MATERIALS.
Ventilation:PROVIDE LOCAL EXHAUST/MECHANICAL VENTILATION TO KEEP Protective Gloves:RECOMMENDED
Eye Protection:SAFETY GLASSES W/UNPERFORATED SIDESHIELD
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE.
Supplemental Safety and Health
WT PER GAL: 10.2-11.6 LBS. THIS COATING CONTAINS MATERIALS CLASSIFIED
AS NUISANCE PARTICULATES, FOR EXAMPLE TITANIUM DIOXIDE, CALCIUM
CARBONATE WHICH MAY BE PRESENT AT HAZARDOUS LEVELS ONLY DURING SAN
DING & ABRADING OF THE DRIED FILM.

Chemical Properties

Boiling Pt:B.P. Text:212-388F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:62-67%

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:EXTREME HEAT
Hazardous Decomposition Products:CO2, CO, OXIDES OF METALS

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DON'T
INCINERATE CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE W/FEDERAL,
STATE, & LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.