

## **A6 R17 BASE D FLAT LATEX HOUSE/TRIM PAINT**

### **MSDS Number**

BBXJN

### **National Stock Number**

8010-00F007163

### **Product Name**

A6 R17 BASE D FLAT LATEX HOUSE/TRIM PAINT

### **Manufacturer**

SHERWIN WILLIAMS COMPANY

### **Product Identification**

Product ID:A6 R17 BASE D FLAT LATEX HOUSE/TRIM PAINT

MSDS Date:04/10/1985

FSC:8010

NIIN:00F007163

MSDS Number: BBXJN

### **Responsible Party**

SHERWIN-WILLIAMS COMPANY

101 PROSPECT AVENUE N.W.

CLEVELAND , OH 44115

Emergency Phone: (216) 556-2917

Info Phone: (216) 556-2902

Cage: 54636

### **Contractor**

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

### **Ingredients**

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 0-5%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

ANTIMONY (SARA III)

CAS: 7440-36-0

RTECS: CC4025000

Fraction By Weight: 0-1%

OSHA PEL0.5 MG/M3

ACGIH TLV: 0.5 MG SB/M3; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: IN A CONFINED AREA VAPORS  
IN HIGH CONCENTRATION ARE ANESTHETIC. MAY RESULT IN  
LIGHTHEADEDNESS, STAGGERING GAIT, & IRRITATION TO THE UPPER  
RESPIRATORY SYSTEM. SKIN: IRRITATION.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:INHALATION: IN A CONFINED AREA VAPORS IN HIGH  
CONCENTRATION AREA ANESTHETIC. MAY RESULT IN LIGHTHEADEDNESS,  
STAGGERING GAIT, & IRRITATION TO THE UPPER RESPIRATORY SYSTEM.  
SKIN: IRRITATION.

## First Aid

First Aid:INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE  
BREATHING. KEEP WARM/QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY  
W/SOAP & WATER. REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.  
EYES: FLUSH W/ LARGE AMOUNTS OF WATER FOR 15 MINTUES. GET MEDICAL  
ATTENTION. INGESTION: GET MEDICAL ATTENTION.

## Fire Fighting

Flash Point Method:PMCC  
Flash Point:>199F  
Extinguishing Media:CO2, DRY CHEMICAL, ALCOHOL FOAM  
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT/SCBA. WATER SPRAY  
MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.  
Unusual Fire/Explosion Hazard:WATER MAY BE USED TO COOL CLOSED  
CONTAINERS TO PREVENT PRESSURE BUILD-UP & POSSIBLE AUTOIGNITION OR  
EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE &  
REMOVE W/INERT ABSORBENT.

## Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.  
DON'T TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. TRANSFER  
ONLY TO APPROVED CONTAINERS W/LABELING.  
Other Precautions:PROTECT AGAINST HAZARDOUS DUST OR FUMES WHICH MAY BE  
GENERATED BY SANDING, ABRADING, BURNING, BRASING OR WELDING DRIED  
FILM. USE ONLY W/ADEQUATE VENTILATION. AVOID BREATHING VAPOR/SPRAY  
MIST & CONTACT W/SKIN & EYES. WASH HANDS AFTER USING.

## Exposure Controls

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BY VENTILATION, WEAR RESPIRATORY DEVICE APPROVED BY NIOSH/M  
PROTECTION AGAINST MATERIALS.  
Ventilation:PROVIDE LOCAL EXHAUST/MECHANICAL VENTILATION TO KEEP Protective Gloves:RECOMMENDED  
Eye Protection:SAFETY GLASSES W/UNPERFORATED SIDESHEILD  
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE.  
Supplemental Safety and Health  
WT PER GAL: 10.2-11.6 LBS. THIS COATING CONTAINS MATERIALS CLASSIFIED  
AS NUISANCE PARTICULATES, FOR EXAMPLE TITANIUM DIOXIDE, CALCIUM  
CARBONATE WHICH MAY BE PRESENT AT HAZARDOUS LEVELS ONLY DURING SAN  
DING & ABRADING OF THE DRIED FILM.

## Chemical Properties

Boiling Pt:B.P. Text:212-388F  
Vapor Density:>AIR  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:62-67%

## Stability

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:EXTREME HEAT  
Hazardous Decomposition Products:CO2, CO, OXIDES OF METALS

## Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DON'T  
INCINERATE CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE W/FEDERAL,  
STATE, & LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):

---

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.