

# V-100 EPOXY GROUT STANDARD FORMULA

## **MSDS Number**

**BBXMK** 

#### **National Stock Number**

8030-00F007223

#### **Product Name**

V-100 EPOXY GROUT STANDARD FORMULA

#### Manufacturer

UNISORB MACHINERY INST

#### **Product Identification**

Product ID:V-100 EPOXY GROUT STANDARD FORMULA MSDS Date:01/01/1987 FSC:8030 NIIN:00F007223 MSDS Number: BBXMK

# **Responsible Party**

UNISORB MACHINERY INST/JACKSON, MI 49204

Emergency Phone: (517) 764-6060

Cage: 64128

Contractor

UNISORB INSTALLATION TECHNOLOGIES

1000

JACKSON, MI 49204-1000

517-764-6060

US

Cage: 64128

#### **Ingredients**

**EPOXY RESIN (25-35%)** 

CAS: 25068-38-6 RTECS: KC2100000 Fraction By Weight: 35%

# Hazards

Effects of Overexposure: MILDLY IRRITATING TO EYES/SKIN. EXCESSIVE INHALATION MAY CAUSE DIZZINESS, RASH.

#### First Aid

First Aid:EYE: FLUSH WITH WATER. OBTAIN MEDICAL ATTENTION. SKIN: WASH WITH SOAP & WATER. INHALATION: MOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION.

# **Fire Fighting**

Flash Point:>200F (CC)

Extinguishing Media: FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures: FULL PROTECTIVE EQUIPMENT W/BREATHING

APAARATUS.

Unusual Fire/Explosion Hazard:NONE

## **Accidental Release**



Spill Release Procedures: SPREAD ABSORBENT MATERIAL OVER AREA. WIPE OR SCRAPE UP MATERIAL. WASH AREA WITH SOAP WATER. (PREVENT FROM ENTERING SEWERS & WATERWAYS).

# Handling

Handling and Storage Precautions:STORE IN A COOL (60-80F) DRY PLACE. Other Precautions:SOILED CLOTHING SHOULD BE REMOVED AND WASHED. LEATHER ARTICLES SHOULD BE DESTROYED.

# **Exposure Controls**

Respiratory Protection: NIOSH APPROVED RESPIRATORS SHOULD BE USED IN

CONFINED AREAS.

Ventilation:LOCAL EXHAUST

Protective Gloves: RUBBER/NEOPRENE

Eye Protection: GLASSES/GOGGLES/FACE MASK

Other Protective Equipment: BODY COVERING CLOTHING OR BARRIER CREAM.

Supplemental Safety and Health

MSDS DATE: 05/86.

# **Chemical Properties**

Boiling Pt:B.P. Text:>200F

Vapor Density:>1 Spec Gravity:1.77

Evaporation Rate & Reference: SLOWER THAN ETHER Appearance and Odor: TAN VISCIOUS LIQUID - MILD ODOR.

### **Stability**

Stability Indicator/Materials to Avoid:YES ACIDS, STRONG OXIDANTS, (ALDEHYDES, CO2, & CO) Stability Condition to Avoid:CONTACT W/AMINE CPDS UNDER UNCONTROLLED CONDITIONS.

Hazardous Decomposition Products: TOXIC FUMES MAY DEVELOP IF INCINERATED Conditions to Avoid Polymerization: CONTACT W/AMINE CPDS UNDER UNCONTROLLED CONDITIONS.

### **Disposal**

Waste Disposal Methods: BURY IN AN APPROVED LANDFILL IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.