

POLY LEASE

MSDS Number

BCBFD

National Stock Number

6850-00K000614

Product Name

POLY LEASE

Manufacturer

ALLIED CHEMICAL CORP

Product Identification

Product ID: POLY LEASE
MSDS Date: 01/01/1985
FSC: 6850
NIIN: 00K000614
MSDS Number: BCBFD

Responsible Party

ALLIED CHEMICAL CORPORATION
COLUMBIA RD & PARK AVE
MORRISTOWN , NJ 07960
US

Cage: 1L168

Contractor

ALLIED-SIGNAL INC
1087R
MORRISTOWN, NJ 07962-2332
US
201-455-4414
Cage: 1L164

Ingredients

DICHLORODIFLUOROMETHANE (SARA III)
CAS: 75-71-8
RTECS: PA8200000
Fraction By Weight: 35%
OSHA PEL1000 PPM
ACGIH TLV: 1000 PPM; 9192
EPA Report Quantity: 5000 LBS
DOT Report Quantity: 5000 LBS

METHYLENE CHLORIDE (SARA III)
CAS: 75-09-2
RTECS: PA8050000
Fraction By Weight: 7%
OSHA PEL500 PPM/C,1000; Z2

ACGIH TLV: 50 PPM, A2; 9192
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6
RTECS: DE3030000
Fraction By Weight: 20%
OSHA PEL100 PPM

TRICHLOROFLUOROMETHANE (CFC-11) (SARA III)

CAS: 75-69-4
RTECS: PB6125000
Fraction By Weight: 35%
OSHA PEL1000 PPM
ACGIH TLV: C, 1000 PPM; 9293
EPA Report Quantity: 5000 LBS
DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure:EYES/SKIN:IRRITNT.BRTHG:HIGH CONCS CAUSES
CARDIAC ARRYTHMIA,ASPHYX,INGEST:NAUS,VOMIT.

First Aid

First Aid:INHALED:REMOVE TO FRESH AIR.GIVE CPR IF NECESSARY.EYES:FLUSH
THOROUGHLY WITH WATER.SKIN:WASH WITH SOAP AND WATER.

Fire Fighting

Flash Point:N/A FOR AEROSOL
Lower Limits:UNK
Upper Limits:UNK
Extinguishing Media:CO*2,ALC FOAM,DRY CHEMICAL
Fire Fighting Procedures:STOP LEAK.WATER STREAM TO COOL EXPOSED
CONTAINERS
Unusual Fire/Explosion Hazard:IF LEAKING,V & P NAPHTHA IS VERY
FLAMMABLE AND VAPORIZES TO A VERY FLAMMABLE GAS.

Accidental Release

Spill Release Procedures:(CONTAINED IN AEROSAL CANS).ELIMINATE IGNITION
SOURCES.ALLOW TO EVAPORATE AND HARDEN.SRAPE UP RESIDUAL WAX
COATING AND DISCARD

Handling

Handling and Storage Precautions:STORE AT AMBIENT TEMP.AWAY FROM HEAT
AND SUN.NO SMOKING ALLOWED WHEN USING.KEEP AREA FREE OF IGNITION
SOURCES
Other Precautions:HALOGENATED HYDROCARBONS IN CONFINED/ENCLOSED SPACES
REQUIRE WELL-VENTILATED DRAFT AS THEY VAPORIZE READILY EVAPORATE
AND DISPLACE OXYGEN WHICH IS NECESSARY FOR BREATHING.

Exposure Controls

Respiratory Protection:NOT GENERALLY REQUIRED
Ventilation:LOCAL EXHAUST/MECHAN ADEQUATE TO MAINTN EXPOSURE BELOW TLVS
Protective Gloves:NOT GEN'L REQD
Eye Protection:CHEM SAFETY GOGGLES
Other Protective Equipment:NOT GENERALLY REQUIRED

Supplemental Safety and Health
FLASHPOINT 50F TCC IS PROBABLY FOR COMPONENT-NAPHTHA.ITEM IS NO LONGER
MANUFACTURED BY ALLIED CHEM.NO DATA ON HAZARDOUS INGREDIENTS
AVAILABLE FROM MGF OR SUBSIDIARIES(PLASKON)

Chemical Properties

HCC:G3
Boiling Pt:B.P. Text:SEE ADD DAT
Vapor Pres:UNK
Vapor Density:UNK
Spec Gravity:1.0
Appearance and Odor:COLORLESS LIQUID,CLOUDY,LEAVING WAXY,CLEAR COATING
Percent Volatiles by Volume:96

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:NONE LISTED
Hazardous Decomposition Products:GEN'L UNKNOWN.EXPECT CO,CO*2,STEAM

Disposal

Waste Disposal Methods:SINCE IT IS A MATTER OF DISPOSAL OF AEROSOL
CANS,DISPOSE IN ACCORDANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.