

TURCO FORM MASK 522

MSDS Number

ВСВНМ

National Stock Number

6850-00K000675

Product Name

TURCO FORM MASK 522

Manufacturer

TURCO PRODUCTS INC

Product Identification

Product ID:TURCO FORM MASK 522 MSDS Date:01/01/1985 FSC:6850 NIIN:00K000675 MSDS Number: BCBHM

Responsible Party

TURCO PRODUCTS, INC

24700 SOUTH MAIN STREET

CARSON , CA 90749

US

Emergency Phone: 614-387-6200

Info Phone: 714-890-3600

Cage: D9808 **Contractor**

TURCO PRODUCTS, INC.

6200

PHILADELPHIA, PA 19103

US

215-419-7890

Cage: D9808

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 40.0% OSHA PEL200 PPM/150 STEL ACGIH TLV: 50 PPM; 9293 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7 RTECS: ZE2100000



Fraction By Weight: 10.0% OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS: 8002-05-9 RTECS: SE7449000

Fraction By Weight: 15.0%

OSHA PEL400 PPM

ACGIH TLV: 400 PPM; 8990

Hazards

Effects of Overexposure:INH:HEAD,NOSE/THROAT IRRIT;EYES:SEV IRRIT MAY DAMAGE PERMANTLY;SKIN:IRRIT,DEFATNG,MAY ABSORB TOX AMT

First Aid

First Aid:SKIN:WASH W SOAP & WATER,GET MED ATTN. IF IRRIT/BLISTRNG OCCUR:EYES:FLUSH W LG VOL OF WATER;INH:REMOVE TO FRESH AIR,GIVE CPR/OXYGEN IF NECESS;ING:DO NOT INDUCE VOMIT,GIVE LG VOL OF MILK/WATER;CALL PHY S FOR ANY OF ABOVE PROBLEM;TAKE TO HOSPIF NECESSA

Fire Fighting

Flash Point:40F TCC Lower Limits:1.3 Upper Limits:6.8

Extinguishing Media:CO*2,FOAM,DRY CHEM

Fire Fighting Procedures: USE SELF-CNTND BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: NONE KNOWN

Accidental Release

Spill Release Procedures: VENTILATE AREA. WEAR PROTECTVE EQUIP. ELEMINATE IGN SOURCE. STOP LEAK W/O RISK. DIKE/CONTAIN SPILLAGE. WIPE UP OR ABSORB SPILLAGE ONTO ABSORBENT MATL. RECOVER IN DRUMS/CONTNRS WHICH ARE SUITABLE FOR SHIPMEN T TO DISPOSAL LOCATION.

Handling

Handling and Storage Precautions: STORE AWAY FROM HEAT/IGN SOURCES.USE CAR IN OPENING DRUMS TO AVOID SPURTING OF CONTENTS.PROTECT CONTNRS AGAINST PHYSICAL DAMAGE.

Other Precautions:VAPO HEAVR THAN AIR WILL TRAVL ALONG GRD COLLECTING IN LOW AREAS SUCH AS SUMPS.PERSONS ENTERING THIS AREA SHOULD USE PROTECT EQUIP & BE OBSERVED WHILE IN THE AREA;AVOID REPEATD CONT W SKIN/EYE

Exposure Controls

Respiratory Protection: SELF-CNTND BRTHG APP, POS PRESSURE HOSE

MASK/AIR-LINE MASK W/FACEPIEC

Ventilation: LOCAL EXHAUST TO MINIMIZE VAPOR CONCENTRATION.

Protective Gloves: NEOPRENE

Eye Protection: CUP TYPE/RUBBR FRAMD GOGG

Other Protective Equipment: SOLVENT RESISTANT BOOTS & APRON(NEOPRENE)

Supplemental Safety and Health

Chemical Properties

HCC:F3

Boiling Pt:B.P. Text:220F



Vapor Pres:40M Vapor Density:>1.0 Spec Gravity:0.97

Evaporation Rate & Reference: 1.0(BU ACETATE)

Solubility in Water: NEGLIGIBLE

Appearance and Odor: TAN VISCOUS LIQUID, AROMATIC ODOR.

Percent Volatiles by Volume: 70.0

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING & CORROSIVE MATL. Stability Condition to Avoid:SOURCE OF FLAME,IGNIT Hazardous Decomposition Products:OXIDES OF CARBON & NITROGEN,CARBON MONOXIDE

Disposal

Waste Disposal Methods:MFGR RECOMMENDS ONE OR ALL OF THE FOLLOWING METHODS;(1) INCINERATE IN AN APPRVD INCINERATOR W FUME SCRUBBER(2)LANDFILL IAW LOCAL,STATE,FED REGS;(3) TRANSFER/SHIP TO RECLAIMING FACILITY FOR SOLVENT REC OVER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.