

TURCO 4367

MSDS Number

BCBJM

National Stock Number

6850-00K000706

Product Name

TURCO 4367

Manufacturer

TURCO PRODUCTS INC

Product Identification

Product ID: TURCO 4367

MSDS Date: 01/01/1985

FSC: 6850

NIIN: 00K000706

MSDS Number: BCBJM

Responsible Party

TURCO PRODUCTS, INC

24700 SOUTH MAIN STREET

CARSON, CA 90749

US

Emergency Phone: 614-387-6200

Info Phone: 714-890-3600

Cage: D9808

Contractor

TURCO PRODUCTS, INC.

6200

PHILADELPHIA, PA 19103

US

215-419-7890

Cage: D9808

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 80.0%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 10.0%
OSHA PEL200 PPM/300 STEL
ACGIH TLV: 200 PPM/300STEL 9192
EPA Report Quantity: 5000 LBS
DOT Report Quantity: 5000 LBS

ALUMINUM SILICATE (AS NUISANCE DUST OR PARTICULATES NOT
CAS: 1302-76-7
RTECS: BD1450000
Fraction By Weight: 5.0%
OSHA PEL15 MG/M3 TOTAL DUST
ACGIH TLV: 10 MG/M3 TDUST;8990

METHYL METHACRYLATE (SARA III)
CAS: 80-62-6
RTECS: OZ5075000
Fraction By Weight: 5.0%
OSHA PEL100 PPM
ACGIH TLV: 100 PPM; 9192
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:SKIN:IRRIT,DEFAT,POSS INFLAMATION;EYES:SEV
IRRIT;ING:NAUSEA;INH:HEAD,DIZZ,IRRIT OF RESP TRACT.

First Aid

First Aid:SKIN:WASH THOROUGHLY W SOAP & WATER;EYES:WASH OUT IMMED.
W/PLENTY OF WATER.GET MEDICAL ATTN;INHALATION:REMOVE AFFECTED
INDIVIDUAL TO FRESH AIR;INGESTION:IMMED GET MEDICAL HELP.DO NOT
INDUCE VOMITING.

Fire Fighting

Flash Point:40F TCC
Autoignition Temp:Autoignition Temp Text:1026F
Lower Limits:UNK
Upper Limits:UNK
Extinguishing Media:CARBON DIOXIDE,FOAM,DRY CHEM.
Fire Fighting Procedures:USE SELF-CNTND BRTHG APP
Unusual Fire/Explosion Hazard:MOD DANGEROUS;WHEN HEATED TO
DECOMPOSITION EMITS TOXIC FUMES; CAN REACT VIGOROUSLY W/OXIDIZING
MATLS

Accidental Release

Spill Release Procedures:WEAR PROTECTIVE EQUIP,STOP LEAK W/O
RISK.ELIMINATE SOURCE OF IGN.SOAK UP ON ABSORBEN MATL. SWEEP &
PLACE IN SEALABLE CNTNRS.LG AMT OF SPILLAGE SHOULD BE DIKED,LIQ
PUMPED INTO SELALBLE SALVAGE TANKS.RE MAINING LIQ BE ABSORBED ON
ABSORBENT & PLACE IN CO

Handling

Handling and Storage Precautions:STORE & USE IN WELL VENTILATED AREAS
BELOW TEMP 130F.KEEP AWAY FROM SOURCES OF IGNITION & STRONG
OXIDIZING MATLS.

Other Precautions: AVOID REPEATED/PROLONGED SKIN CONTACT.

Exposure Controls

Respiratory Protection: FRESH AIR TYPE OR GAS MASK W/USBM APPRVD
CANISTER

Ventilation: LOCAL EXHAUST

Protective Gloves: RESISTANT

Eye Protection: SPLASH GOGGLES

Supplemental Safety and Health

Chemical Properties

HCC: F3

Boiling Pt: B.P. Text: 180F

Vapor Pres: 50

Vapor Density: >1.0

Spec Gravity: 0.89

Evaporation Rate & Reference: >1.0 (BU ACETATE)

Solubility in Water: MODERATE

Appearance and Odor: SLIGHTLY VISCOUS ORANGE LIQUID, TOLUENE ODOR.

Percent Volatiles by Volume: 90

Stability

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS,, CORROSIVE MATL

Stability Condition to Avoid: SOURCE OF IGN

Hazardous Decomposition Products: OXIDES OF CARBON

Disposal

Waste Disposal Methods: SEPARATE THE LIQUID PORTION & INCINERATE OR
DISPOSE IN AN APPROVED LANDFILL IAW APPLICABLE FEDERAL, STATE, OR
LOCAL REGULATIONS. INCINERATION SHOULD BE DONE PER APCD REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.