

## **TURCO 4454**

### **MSDS Number**

BCBJT

### **National Stock Number**

6850-00K000711

### **Product Name**

TURCO 4454

### **Manufacturer**

TURCO PRODUCTS INC

### **Product Identification**

Product ID:TURCO 4454

MSDS Date:01/01/1985

FSC:6850

NIIN:00K000711

MSDS Number: BCBJT

### **Responsible Party**

TURCO PRODUCTS,INC

Emergency Phone: 213-634-3300

Cage: D9808

### **Contractor**

TURCO PRODUCTS,INC.

6200

PHILADELPHIA, PA 19103

US

215-419-7890

Cage: D9808

### **Ingredients**

DIESEL FUELS(TYPE NOT SPECIFIED)

Fraction By Weight: 50.0%

ACGIH TLV: 200PPM(PER MFR)

NON-FLAMMABLE OILS(TYPE NOT SPECIFIED)

Fraction By Weight: 50.0%

### **Hazards**

Effects of Overexposure:EYES:MOD IRRIT,REDNESS,TEAR;SKIN:MOD IRRIT;INH:MOD IRRIT IF INHALED MIST;ING:THROAT/ESOPHAGUS DAMAGE

### **First Aid**

First Aid:SKIN/EYES:FLUSH W/WATER.GET MED ATTN IF IRRIT PERSISTS;ING:DO NOT INDUCE VOMITING.GET MED HELP;INH:REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT,GIVE OXYGEN/CPR.CALL A DR.

### **Fire Fighting**

Flash Point:160F TCC

Extinguishing Media:CO\*2,CHEMICAL FOAM

Fire Fighting Procedures:USE SELF CNTND BRTHG APP

Unusual Fire/Explosion Hazard:NONE

## Accidental Release

Spill Release Procedures:WEAR PROTECTIVE EQUIP,STOP LEAD W/O RISK.ELIMINATE SOURCE OF IGN.SOAK UP ON ABSORBEN MATL.SWEEP & PLACE IN SEALABLE CNTNRS.LG AMT OF SPILLAGE SHOULD BE DIKED,LIQ PUMPED INTO SEALABLE SALVAGE TANKS.REM AINING LIQ BE ABSORBED ON ABSORBENT & PLACE IN CON

## Handling

Handling and Storage Precautions:STORE IN CLOSED CONTAINERS AT A TEMPERATURE BETWEEN 30F & 120F.

## Exposure Controls

Respiratory Protection:RESPIRATOR W/ORGANIC VAP CANISTER IF VAPOR CONC IS OVER TLV.

Ventilation:LOCAL EXHAUST

Protective Gloves:RESISTANT

Eye Protection:GOGGLES

Supplemental Safety and Health

PER MFGR 9/30/82,THE PRODUCT HAS FLASH PT 160F BECAUSE IT CONTAINS APPRX 50% DIESEL FUEL OIL & 50% OTHER NON-FLAMM OILS.THESE ARE NOT CITED IN MSDS AS THEY ARE NOT CONSIDERED TOXIC TO HEALTH.

## Chemical Properties

HCC:V4

Boiling Pt:B.P. Text:300F

Vapor Pres:10

Vapor Density:> 1.0

Spec Gravity:0.88

Evaporation Rate & Reference:Solubility in Water:EMULSIFIES

Appearance and Odor:CLEAR, AMBER LIQUID

Percent Volatiles by Volume:50

## Stability

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZERS/CORROSIVE.

Stability Condition to Avoid:SOURCE OF IGN.

Hazardous Decomposition Products:OXIDES OF CARBON

## Disposal

Waste Disposal Methods:SEPARATE THE LIQUID PORTION & INCINERATE OR DISPOSE IN AN APPROVED LANDFILL IAW APPLICABLE FEDERAL,STATE,OR LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.