

## **TURCO 5292B**

### **MSDS Number**

BCBJZ

### **National Stock Number**

6850-00K000722

### **Product Name**

TURCO 5292B

### **Manufacturer**

TURCO PRODUCTS INC

### **Product Identification**

Product ID: TURCO 5292B  
MSDS Date: 01/01/1985  
FSC: 6850  
NIIN: 00K000722  
MSDS Number: BCBJZ

### **Responsible Party**

TURCO PRODUCTS, INC.  
24700 SOUTH MAIN STREET  
CARSON, CA 90749  
US  
Emergency Phone: 614-387-6200  
Info Phone: 714-890-3600  
Preparer: NOT PROVIDED.  
Cage: D9808

### **Contractor**

TURCO PRODUCTS, INC.  
6200  
PHILADELPHIA, PA 19103  
US  
215-419-7890  
Cage: D9808

### **Ingredients**

METHYLENE CHLORIDE (SARA III)  
CAS: 75-09-2  
RTECS: PA8050000  
Fraction By Weight: 60.0%  
OSHA PEL500 PPM/C, 1000; Z2  
ACGIH TLV: 50 PPM, A2; 9192  
EPA Report Quantity: 1000 LBS  
DOT Report Quantity: 1000 LBS

PHENOL

CAS: 108-95-2

RTECS: SJ3325000

Fraction By Weight: 25.0%

OSHA PELS, 5 PPM

ACGIH TLV: S, 5 PPM; 8990

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TALL OIL SOAP

Fraction By Weight: 10.0%

SODIUM CHROMATE (SARA III)

CAS: 7775-11-3

RTECS: GB2955000

Fraction By Weight:

OSHA PEL0.1 PPM CRO3;CEILING

ACGIH TLV: 0.05 MG CR/M3; 9192

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

WAX & METHOCEL THICKENER

Fraction By Weight: 1.0%

## Hazards

Effects of Overexposure:INH:HEAD,DIZZ,RESP IRRIT;ING:BURNS  
THROAT,MOUTH,EXOPHAGUS;EYES:SEV IRRIT,CORNEAL \*SEE SUPPL DATA\*

## First Aid

First Aid:EYES:FLUSH WELL W/WATER.GET MED ATTN IMMED;SKIN:FLUSH AREA  
W/ISOPROPANOL.THEN WASH W/SOAP & WATER. GET MED ATTN IF IRRIT  
PERSISTS;INH:MOVE TO FRESH AIR.GIVE OXYGEN/CPR IF NEEDED.GET MD  
HELP;ING:GIVE L G QTY OF WATER.GET MED ATTN.

## Fire Fighting

Flash Point:NONE

Lower Limits:UNK

Upper Limits:UNK

Extinguishing Media:CO\*2

Fire Fighting Procedures:NONE KNOWN

Unusual Fire/Explosion Hazard:THERMAL DECOMPOSITION WILL PRODUCE TOXIC  
GASES.WEAR GAS MASK.

## Accidental Release

Spill Release Procedures:VENTILATE AREA.STOP LEAK W/O RISK.ABSORB  
SPILLAGE W/SWEEPING COMPOUND OR SAWDUST.& PLACE IN A SEALABLE  
CONTAINER.

## Handling

Handling and Storage Precautions:AVOID CONTACT W/SKIN & CLOTHING.USE  
W/ADEQUATE VENTILATION.STORE UNDER CONTROLLED TEMP BETWEEN 32F TO  
100F.

Other Precautions:OPEN CONTAINER CAUTIOUSLY TO AVOID SPURTING.

## Exposure Controls

Respiratory Protection: GAS MASK W/USBM APPRVD CANISTER W/SOURCE OF AIR  
IF TLV EXCEEDS LIMIT  
Ventilation: LOCAL EXHAUST  
Protective Gloves: RESISTANT  
Eye Protection: FACE SHIELD  
Other Protective Equipment: SOLVENT RESISTANT APRON  
Supplemental Safety and Health  
\*DAMAGE; SKIN: SEV IRRIT, DIZZ INCREASED LEVELS OF BLOOD  
CARBOXYLHEMOGLOBIN; CHROMIC: MAY CAUSE DAMAGE TO LIVER, KIDNEYS  
PANCREAS; HAZ INGREDIENICE: BALANCE IS WATER IN THE MIXTURE.

## Chemical Properties

HCC: T3  
Boiling Pt: = 37.8C, 100.F  
Vapor Pres: 350  
Vapor Density: > 1.0  
Spec Gravity: 1.20  
Evaporation Rate & Reference: > 1.0 (BU-ACETATE)  
Solubility in Water: APPRECIABLE  
Appearance and Odor: VISCOUS BROWN LIQ, SPICEY ODOR  
Percent Volatiles by Volume: 60.0

## Stability

Stability Indicator/Materials to Avoid: YES  
STRONG OXIDIZERS  
Hazardous Decomposition Products: OXIDES OF CHLORINE & CARBON

## Disposal

Waste Disposal Methods: TRANSPORT TO APPROVED INDUSTRIAL DUMP FOR  
DISPOSAL IAW FED, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.