

TURCO DY-CHEK PENETRANT

MSDS Number

BCBLB

National Stock Number

6850-00K000766

Product Name

TURCO DY-CHEK PENETRANT

Manufacturer

TURCO PRODUCTS INC

Product Identification

Product ID: TURCO DY-CHEK PENETRANT

MSDS Date: 01/01/1985

FSC: 6850

NIIN: 00K000766

MSDS Number: BCBLB

Responsible Party

TURCO PRODUCTS, INC.

24700 SOUTH MAIN STREET

CARSON, CA 90749

US

Emergency Phone: 614-387-6200

Info Phone: 714-890-3600

Cage: D9808

Contractor

TURCO PRODUCTS, INC.

6200

PHILADELPHIA, PA 19103

US

215-419-7890

Cage: D9808

Ingredients

ALIPHATIC PETROLEUM SOLVENT (CAS #8002-05-9)

Fraction By Weight: 55.0%

ACGIH TLV: 350 PPM

DIBUTYL PHTHALATE (SARA III)

CAS: 84-74-2

RTECS: TI0875000

Fraction By Weight: 40.0%

OSHA PEL5 MG/M3

ACGIH TLV: 5 MG/M3; 9192

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

Hazards

Effects of Overexposure:EYES:MOD IRRIT,REDNESS/TEAR;SKIN:MOD IRRIT,DRY;INH:MOD IRRIT IF MIST INHALED;*SEE OTHER PRECAUTIONS.

First Aid

First Aid:SKIN/EYES:FLUSH W/WATER.IF IRRITATION PERSISTS, CALL A DR.ING:DO NOT INDUCE VOMITING.GET MED ATTN IMMED;INH:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,GIVE OXYGEN & GET MED HELP AT ONCE.

Fire Fighting

Flash Point:140F TCC
Lower Limits:UNK
Upper Limits:UNK
Extinguishing Media:CARBON DIOXIDE
Fire Fighting Procedures:NONE KNOWN
Unusual Fire/Explosion Hazard:NONE KNOWN

Accidental Release

Spill Release Procedures:VENTILATE AREA.ELIMINATE SOURCE OF IGN.WEAR PROTECTIVE EQUIP.DAM UP W/SANDBAGS OR SOAK UP ON ABSORBENT MATERIALS.PUMP LIQ &/OR SWEEP ABSORBED LIQ INTO SEALABLE CONTAINERS.

Handling

Handling and Storage Precautions:STORE IN CLOSED CONTAINERS AT A TEMPERATURE BETWEEN 30 & 120F.
Other Precautions:*EFFECTS OVEREXPOSURE;INGESTION:DAMAGE TO THROAT ESOPHOGAS.

Exposure Controls

Respiratory Protection:RESPIRATOR W/MECHANICAL FILTER FOR MIST CONDITIONS.
Ventilation:LOCAL./MECHANICAL (GEN)
Protective Gloves:RESISTANT
Eye Protection:CHEM SPLASH GOGGLES
Supplemental Safety and Health
CAS #8002-05-9 LISTED FOR PETROLEUM DISTILLATE.

Chemical Properties

HCC:V4
Boiling Pt:B.P. Text:370F
Vapor Pres:UNK
Vapor Density:>1.0
Spec Gravity:0.89
Evaporation Rate & Reference:Solubility in Water:NEGLIGIBLE
Appearance and Odor:DEEP RED LIQ;DI-BUTYL PHTHALATE ODOR
Percent Volatiles by Volume:55.0

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS & CORROSIVES
Stability Condition to Avoid:SOURCE OF FLAME/IGN.
Hazardous Decomposition Products:CARBON DIOXIDE
Conditions to Avoid Polymerization:UNK

Disposal

Waste Disposal Methods:INCINERATE LIQ IN AN APPROVED INCINERATOR OR DISPOSE OF IN THE APPROVED LANDFILL IAW APPLICABLE FEDERAL,STATE & LOCAL REGULATIONS.(IF MIXED W/WATER SEPARATE OUT OIL FRACTION)

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.