

4-BUTYROLACTONE 6922

MSDS Number

BCBMM

National Stock Number

6810-00K000813

Product Name

4-BUTYROLACTONE 6922

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID:4-BUTYROLACTONE 6922

MSDS Date:01/01/1985

FSC:6810

NIIN:00K000813

MSDS Number: BCBMM

Responsible Party

EASTMAN KODAK COMPANY

Emergency Phone: 716-722-0271

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

4-BUTYROLACTONE (CAS #96-48-0)

CAS: 96-48-0

RTECS: LU3500000

Fraction By Weight: 100%

Hazards

Effects of Overexposure:SKIN:MILD IRRITATION;INH:HIGH VAP
CONCENTRATIONS MAY PRODUCE ANESTHETIC EFFECT.

First Aid

First Aid:PER MANUFACTURER MSDS,NONE SEEM SPECIFICALLY
INDICATED.NOTHING IS KNOWN OF THE EFFECTS OF REPEATED LONG TERM
EXPOSURE.HOWEVER,IN CASE OF SKIN CONTACT,FLUSH SKIN W/PLENTY OF
WATER & REMOVE FROM EXPOSUR E AREA.

Fire Fighting

Flash Point:205F-TCC

Lower Limits:2.1%

Upper Limits:13.4

Extinguishing Media:WATER,FOAM,CO*2,DRY CHEMICAL

Fire Fighting Procedures:NONE KNOWN

Unusual Fire/Explosion Hazard:NONE KNOWN

Accidental Release

Spill Release Procedures:SM SPILL:ABSORB ON PAPER/VERMICULITE.ALLOW TO EVAPORATE IN HOOD OR IN WELL VENTILATED AREA.BURN RESIDU IN INCINERATOR;LG SPILL:EVACUATE UNPROTECTED PERSONS.STOP LEAK W/O RISK.DIKE LIQUID & PUMP INTO C LOSED DRUMS SUITABLE FOR SHIPMENT.

Handling

Handling and Storage Precautions:NONE KNOWN

Exposure Controls

Respiratory Protection:AIR SUPPLY MASK/SELF-CNTND BREATHING APP FOR LARGE AMOUTNS

Ventilation:LOCAL EXHAUST/MECHANICAL(GENERAL)

Protective Gloves:RUBBER

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:NONE KNOWN

Supplemental Safety and Health

MSDS FROM MFGR DATED:5/14/73.

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:403F(206C)

Vapor Pres:1MM

Vapor Density:3.0

Spec Gravity:1.125

Solubility in Water:SLIGHT(MISC

Appearance and Odor:CLEAR OILY LIQUID;UNPLEASANT ODOR

Percent Volatiles by Volume:100

Stability

Stability Indicator/Materials to Avoid:YES

Disposal

Waste Disposal Methods:DILUTE COLLECTED WASTE LIQ W/FLAMMABLE SOLVENT.SPRAY INTO INCINERATOR EQUIPPED W/AFTERBURNER & SCRUBBER.DISPOSAL MUST BE IN FULL COMPLIANCE WITH FED,STATE & LOCAL REGS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.