

## **121 2588,EKTAPRINT 2 BLEACH-FIX GENERATOR**

### **MSDS Number**

BCBQY

### **National Stock Number**

6750-00K000883

### **Product Name**

121 2588,EKTAPRINT 2 BLEACH-FIX GENERATOR

### **Manufacturer**

EASTMAN KODAK COMPANY

### **Product Identification**

Product ID:121 2588,EKTAPRINT 2 BLEACH-FIX GENERATOR

MSDS Date:01/01/1987

FSC:6750

NIIN:00K000883

MSDS Number: BCBQY

### **Responsible Party**

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

### **Contractor**

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

### **Ingredients**

20-25%

CAS: 7783-18-8

RTECS: XN6465000

Fraction By Weight: 22.5%

TETRAAMMONIUM ETHYLENEDIAMINETETRAACETIC ACID; WT %

Fraction By Weight: 12.5%

ETHYLENEDIAMINE-TETRAACETIC ACID (EDTA) (SARA III)

CAS: 60-00-4

RTECS: AH4025000

Fraction By Weight: 12.5%

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

1-5%

RTECS: WT3505000

Fraction By Weight: 03.0%

50-55%

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 52.5%

## Hazards

Effects of Overexposure:PER MFGR MSDS,LOW HAZARD.;NOT EXPECTED TO BE A PROBLEM;MAINTAIN STRIC HYGIEN.

## First Aid

First Aid:MFGR MSDS STATE,"NONE INDICATED.";HOWEVER,FLUSH W/PLENTY OF WATER IN CASE OF SKIN/EYE CONTACT.GET MEDICAL HELP IF SYMPTOMS OF IRRITATION/DISCOMFORT OCCUR;IF DIFFICULT IN BREATHING,GIVE CPR/OXY & GET M ED ATTN.

## Fire Fighting

Flash Point:NONE

Upper Limits:0201

Extinguishing Media:WEAR SCBA & PROTECTIVE CLOTHING TO PREVENT CLOTHG/SKIN CONTC

Fire Fighting Procedures:FIRE/HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION.

Unusual Fire/Explosion Hazard:CONTAINER MAY EXPLODE IN HEAT OF FIRE;SPILL/RUNOFF MAY CAUSE POLLUTION,FIRE,&/OR EXPLOSION.

## Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.ELIM IGN SOURCES.USE PROTECTV CLOTHNG/SAFETY GLASSES.STOP LEAK W/O RISK.PROVIDE VENT.DIK LG SPILL & PUMP INTO COVRD DRUMS;ABSORB/CONTAIN SM SPILL IN CONT;MFGR RECOMMENDS,F LUSH TO SEWER W/LG AMT OF WATER IAW EXISTING LAWS.

## Handling

Handling and Storage Precautions:STORE IN COOL,DRY PLACE.AVOID EXCESSIVE HEAT.KEEP CONTAINERS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.

Other Precautions:AVOID SKIN/EYE CONTACT W/CHEMICALS.WASH THOROUGHLY AFTER HANDLING;PRODUCT PH:5.4

## Exposure Controls

Respiratory Protection:NONE NEEDED IN NORMAL CONDITIONS

Ventilation:MECHANICAL(GEN)

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:AS REQD BY LOCAL AUTHORITIES.

Supplemental Safety and Health

MSDS FROM KODAK EFFECTV: 10/06/84;PH OF SOLUTION;5.4;SOLN #4332; THIS PRODUCT TAKES PRECEDENCE OVER SIMILAR PROD-BLEACH-FIX REGENERATOR MX 1003-S.KEY1:C1.

## Chemical Properties

HCC:C1

Boiling Pt:B.P. Text:>212F(100C)

Vapor Pres:17

Vapor Density:0.6  
Spec Gravity:1.26  
Solubility in Water:COMPLETE  
Appearance and Odor:SULFUR DIOXIDE ODOR;CLEAR & COLORLESS.  
Percent Volatiles by Volume:54

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG ALKALI  
Stability Condition to Avoid:EXCESSIVE HEAT  
Hazardous Decomposition Products:DECOMPOSES TO OXIDES OF CARBON &  
AMMONIA

## Disposal

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.SHIP  
WASTE MATL TO DISPOSAL FACILITY IAW DOT/EPA REGS.HANDLE/DISPOSE IN  
FULL COMPLIANCE W/ALL INTNL,FED,STATE/LOCAL REGS;MFGR  
RECOMMENDS,FLUSH TO SEWER W/LG A MT OF WATER IAW FED,STATE/LOCAL  
EFFLUENT LAWS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.