

183 2872,EKTPRNT 2 BLCH-FIX & REPL NR, PT A

MSDS Number

BCBRF

National Stock Number

6750-00K000886

Product Name

183 2872,EKTPRNT 2 BLCH-FIX & REPL NR, PT A

Manufacturer

EASTMAN KODAK CO

Product Identification

Product ID:183 2872,EKTPRNT 2 BLCH-FIX & REPL NR, PT A

MSDS Date:10/09/1985

FSC:6750

NIIN:00K000886

Kit Part:Y

MSDS Number: BCBRF

Responsible Party

EASTMAN KODAK CO.

343 STATE ST.

ROCHESTER , NY 14650

Emergency Phone: 716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

AMMONIUM THIOSULFATE

CAS: 7783-18-8

RTECS: XN6475000

Fraction By Weight: 45-50%

SODIUM BISULFITE (SASA III)

CAS: 7631-90-5

RTECS: VZ2000000

Fraction By Weight: 5-10%

OSHA PEL5 MG/M3

ACGIH TLV: 5 MG/M3; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

WATER

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 40-45%

Hazards

Effects of Overexposure:MSDS FM MFR STATES THAT EFFECTS OF OVEREXPOSURE ARE OF LOW HAZARD TO HEALTH

First Aid

First Aid:PER MFR MSDS,"NONE INDICATED.";HOWEVER,FLUSH W/LG AMT OF WATER IN CASE OF SKIN/EYE CONTACT.GET MED ATTN IF NEEDED OR SYMPTOMS OCCUR.

Fire Fighting

Flash Point:NONE

Lower Limits:NONE

Upper Limits:NONE

Extinguishing Media:CO*2,FOAM,DRY CHEM

Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP.

Unusual Fire/Explosion Hazard:NONE KNOWN

Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.ELIM IGN SOURCES.USE PROTECTV CLOTHNG/SAFETY GLASSES.STOP LEAK W/O RISK.PROVIDE VENT.DIKE LG SPILL & PUMP INTO COVRD DRUMS;ABSORB/CONTAIN SM SPILL IN CONT;MFGR RECOMMENDS, FLUSH TO SEWER W/LG AMT OF WATER IAW EXISTING LAWS

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT;AVOID EXCESSIV HEAT
Other Precautions:AVOID PROLONGED/REPEATED CONTACT W/PRODUCT.REMOVE & WASH CONTAMINATED CLOTHING.WASH HANDS AFTER USE;APPROXIMATE PRODUCT PH IS 5.0

Exposure Controls

Respiratory Protection:NONE REQD IN NORMAL CONDITIONS

Ventilation:MECHANICAL(GEN) IF NEEDED

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:AS NEEDED BY LOCAL AUTHORITIES.TO PREVENT SKIN/CLOTHG CONTCT

Supplemental Safety and Health

THIS PRODUCT A/K/A MX1097-2 PART A. THIS IS PART A OF A 2 PART KIT, SEE NSN 6750-00-K00-0920 FOR PART B. BOTH PARTS ARE REQUIRED TO BE MIXED WITH WATER TO FORM 60 GAL WORKING SOLUTION.

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:>212F(100C)

Vapor Pres:17

Vapor Density:0.6

Spec Gravity:1.36

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR,COLORLESS,SLIGHT CHARACTERISTIC SO*2 ODOR

Percent Volatiles by Volume:42

Stability

Stability Indicator/Materials to Avoid:YES

NONE KNOWN

Stability Condition to Avoid:UNK

Hazardous Decomposition Products:UNKNOWN;MAY GIVE OFF SO*2

Disposal

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.SHIP
WASTE MATL TO DISPOSAL FACILITY IAW DOT/EPA REGS.HANDLE/DISPOSE IN
FULL COMPLIANCE W/ALL INTNL,FED,STATE/LOCAL REGS;MFGR
RECOMMENDS,FLUSH TO SEWER W/LG A MT OF WATER IAW FED,STATE/LOCAL
EFFLUENT LAWS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.