

EASTMAN 910 THT ADHESIVE

MSDS Number

BCBSB

National Stock Number

8040-00K000902

Product Name

EASTMAN 910 THT ADHESIVE

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID: EASTMAN 910 THT ADHESIVE MSDS Date: 01/01/1985 FSC:8040 NIIN:00K000902 MSDS Number: BCBSB

Responsible Party

EASTMAN KODAK COMPANY

Emergency Phone: 716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

ALKENYL CYANOACRYLATE Fraction By Weight: 100%

Hazards

Effects of Overexposure: SKIN: POLYMERIZATION OCCURS & BONDS SKIN V.RAPIDLY; EYES: CANBOND EYELIDS; VAP MAY IRRIT MUCUS MEMBRANE

First Aid

First Aid:SKIN:FLUSH IMMED W/H*20 TO CAUSE POLYMERIZATION OF THE MONOMER & REDUCE ITS AFFINITY FOR THE SKIN; EYES: IRRIGATE IMMED & THOROUGHLY W/H*20 HOLDING THE LIDS APART TO PREVENT BONDING.DO NOT FORCE APART I F BONDED.SEE A PHYSICAIAN; INH: REMOVE FROM EXPOSURE

Fire Fighting

Flash Point: UNK (COMBUSTIBLE)

Lower Limits: UNK Upper Limits:UNK

Extinguishing Media:CO*2,DRY CHEM;WATER SPRAY IF POLYMERIZATION NOT

HAZARDOUS.

Unusual Fire/Explosion Hazard: NONE KNOWN

Accidental Release

Spill Release Procedures: ELIM IGNITION SOURCES. SOAK UP ON CLOTHS/ABSORBENT MATL.INCINERATE IMMEDIATLY OR STORE IN A CLOSED METAL CONTAINER.PROTECT EYES, SKIN & CLOTHING BEFORE CLEAN-UP IAW



FED, STATE & LOCAL REGULATIONS.

Handling

VENTILATED/DRY AREA.AVOID WATER/MOISTURE CONTACT W/MATL CONTNRS.AVOID SKIN,EYES & CLOTHING CONTACT.

Other Precautions:USE W/VENTILATION ADEQUATE TO MAINTAIN ATMOSPHERE CONCENTRATION OF VA BELOW IRRITATING LEVEL.IF SKIN BONDNG OCCURD,SOAK IN WARMWATER TO ENHANCE/LOOSENING OF THE BOND.KEEP AWAY FM HEAT/FLAME.

Handling and Storage Precautions: STORE IN TIGHTLY CLOSED CONTAINERS IN

Exposure Controls

Respiratory Protection: A NIOSH APPRVD RESP FOR ORGANIC VAP IF NEEDED; NO NEED IN NORAMLCOND.

Ventilation: LOCAL EXHAUST/MECHANICAL(GEN) RECOMMENDED BY MFR.

Protective Gloves: POLYETHLN/RUBBR Eye Protection: SAFETY GOGGLES/GLASSES.

Other Protective Equipment: AS NEEDED BY LOCAL AUTHORITIES.

Supplemental Safety and Health

MFR MSDS 3/30/73.PROD SOLD TO PERMA-BOND 8/80.PER PERMA-BOND 1/18/84 NO MULTIPLE HAZARDS EXIST.STORE WITH OTHER COMBUSTIBLES.STG CDE BASED ON FLASH PT OF OTHER 910 PRODUCTS.

Chemical Properties

HCC:V4
Boiling Pt:B.P. Text:APPROX 176F
Vapor Pres:UNK
Vapor Density:UNK
Spec Gravity:UNK
Evaporation Rate & Reference:CLEAR LIQUID

Solubility in Water:INSOLUBLE Percent Volatiles by Volume:UNK

Stability

Stability Indicator/Materials to Avoid:NO
OXIDIZING MATL CAN CAUSE A VIGOROUS REACTION
Stability Condition to Avoid:POLYMERIZATION OCCURES BY
WATER/MOISTURE.MAY BE EXOTHERMIC.
Hazardous Decomposition Products:CO,CO*2,OXIDES OF NITROGEN.
Conditions to Avoid Polymerization:MANY COMMON MATLS SUCH AS H*20 CAN POLYMERIZE EXOTHERMALLY.

Disposal

Waste Disposal Methods:INCINERATION OR LANDFILL.MFR SUGGESTED INCINERATE WASTE.OBSERVE ALL FEDERAL,STATE & LOCAL LAWS CONCERNING HEALTH & POLLUTION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.