

120 0104, EKTAPRNT R-100, STBLZR & REPL

MSDS Number

BCBSV

National Stock Number

6750-00K000915

Product Name

120 0104, EKTAPRNT R-100, STBLZR & REPL

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID:120 0104,EKTAPRNT R-100,STBLZR & REPL

MSDS Date:01/01/1985

FSC:6750 NIIN:00K000915

MSDS Number: BCBSV

Responsible Party

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER, NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

716-722-5151/(800) 242-2424

Cage: 19139

US

Ingredients

FORMALDEHYDE (SARA III)

CAS: 50-00-0

RTECS: LP8925000

Fraction By Weight: 12.5% OSHA PELSEE 1910.1048

ACGIH TLV: C 0.3 PPM; A2; 9293 EPA Report Quantity: 100 LBS DOT Report Quantity: 100 LBS

AQUEOUS SOLUTION, HAZARD UNKNOWN, UNIDENTIFIED

Fraction By Weight: 84.5%



CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 3%

OSHA PELS, 200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure: VAPOR /LIQUID IRRITATS EYES, SKIN AND IF INHALED. REPEATED CONTACT MAY RESULT IN ALLERGIC SKIN REACTIO

First Aid

First Aid:INHALATION:REMOVE FROM EXPOSURE.EYES:FOR LIQUID CONTACT,FLUSH WITH WATER 15 MIN.SKIN:FLUSH IMMEDIATELY WITH PLENTY OF WATER.

Fire Fighting

Flash Point: 185F/85C TCC

Extinguishing Media:FOAM,CO*2,DRY CHEMICAL

Fire Fighting Procedures: AVOID INHALING FUMES (FORMALDEHYDE)

Unusual Fire/Explosion Hazard: NOXIOUS ALDEHYDE FUMES.

Accidental Release

Spill Release Procedures: NEUTRALIZE WITH SODIUM BISULFITE THEN FLUSH TO SEWER WITH COPIUS AMOUNTS OF WATER.FEDERAL, STATE AND LOCAL EFFLUENT LAWS TAKE PRECEDENCE.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,PLACE.KEEP CONTAINERS CLOSED.PROTECT FROM PHYSICAL DAMAGE.KEEP IN TIGHTLY SEALED CONTAINERS.

Other Precautions: WASH THOROUGHLY AFTER HANDLING.

Exposure Controls

Respiratory Protection: APPRVD ORGANIC VAPOR RESPIRATOR IF VENTILATION

INADEQUATE

 $Ventilation: {\tt MECHANICAL}({\tt GENERAL})/{\tt LOCAL} \ {\tt EXHAUST} \ {\tt RECOMMENDED}$

Protective Gloves: IMPERVIOUS

Eye Protection: CHEMICAL/SAFETY GOGGLES

Other Protective Equipment: AS NECESSARY TO PREVENT SKIN CONTACT.

Supplemental Safety and Health

PH APPROXIMATELY 3.5.

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:185F/85C

Vapor Pres:32 Vapor Density:1.64 Spec Gravity:1.07

Solubility in Water: COMPLETE

Appearance and Odor:YELLOW-CLEAR,FORMALDEHYDE ODOR

Percent Volatiles by Volume:95

Stability

Stability Indicator/Materials to Avoid:YES

NONE

Hazardous Decomposition Products: NOXIUS FORMALDEHYDE FUMES WHEN HEATED.

Disposal

Waste Disposal Methods: FLUSH TO SEWER WITH COPIUS AMTS OF WATER. FEDERAL, STATE AND LOCAL EFFLUENT LAWS TAKE PRECEDENCE.



Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.