

183 2427,EKTPRNT 2 BLCH-FIX & REPL NR, PT B

MSDS Number

BCBTB

National Stock Number

6750-00K000921

Product Name

183 2427, EKTPRNT 2 BLCH-FIX & REPL NR, PT B

Manufacturer

EASTMAN KODAK CO

Product Identification

Product ID:183 2427, EKTPRNT 2 BLCH-FIX & REPL NR, PT B

MSDS Date:04/04/1983

FSC:6750

NIIN:00K000921

Kit Part:Y

MSDS Number: BCBTB

Responsible Party

EASTMAN KODAK CO.

343 STATE ST.

ROCHESTER, NY 14650

Emergency Phone: 716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

716-722-5151/(800) 242-2424

Cage: 19139

US

Ingredients

AMMONIUM((ETHYLENEDINITRILO)TETRAACETO)-FERRATE (III)

CAS: 21265-50-9

Fraction By Weight: 35-45%

ETHYLENEDIAMINE-TETRAACETIC ACID (EDTA) (SARA III)

CAS: 60-00-4

RTECS: AH4025000

Fraction By Weight: 5-10% EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

WATER

CAS: 7732-18-5 RTECS: ZC0110000



Fraction By Weight: 50-55%

Hazards

Effects of Overexposure: MSDS FM MFR STATES THAT EFFECTS OF OVEREXPOSURE ARE OF LOW HAZARD TO HEALTH.

First Aid

First Aid:PER MFR MSDS,"NONE INDICATED.";HOWEVER,FLUSH W/LG AMT OF WATER IN CASE OF SKIN/EYE CONTACT.GET MED ATTN IF NEEDED OR SYMPTOMS OCCUR.

Fire Fighting

Flash Point:NONE Lower Limits:NONE Upper Limits:NONE

Extinguishing Media:CO*2,FOAM,DRY CHEM

Fire Fighting Procedures: WEAR SELF-CNTND BRTHG APP.

Unusual Fire/Explosion Hazard: NONE KNOWN

Accidental Release

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. ELIM IGN SOURCES. USE PROTECTV CLOTHNG/SAFETY GLASSES. STOP LEAK W/O RISK. PROVIDE VENT. DIKE LG SPILL & PUMP INTO COVRD DRUMS; ABSORB/CONTAIN SM SPILL IN CONT; MFGR RECOMMENDS, FLUSH TO SEWER W/LG AMT OF WATER IAW EXISTING LAWS

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT;AVOID EXCESSIV HEAT Other Precautions:AVOID PROLONGED/REPEATED CONTACT W/PRODUCT.REMOVE & WASH CONTAMINATED CLOTHING.WASH HANDS AFTER USE;APPROXIMATE PRODUCT PH IS 7.0

Exposure Controls

Respiratory Protection: NONE REQD IN NORMAL CONDITIONS.

Ventilation: MECHANICAL (GEN) IF NEEDED

Protective Gloves: IMPERVIOUS Eye Protection: SAFETY GLASSES

Other Protective Equipment: AS NEEDED BY LOCAL AUTHORITIES.

Supplemental Safety and Health

THIS PRODUCT A/K/A MX1097-2 PART B. THIS IS PART B OF A 2 PART KIT, SEE NSN 6750-00-D00-1775 FOR PART A. BOTH PARTS ARE REQUIRED AND MUST BE DILUTED WITH WATER TO MAKE 52 GAL WORKING SOLUTION.

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:>212F(100C)

Vapor Pres:17 Vapor Density:0.6 Spec Gravity:1.25

Solubility in Water: COMPLETE

Appearance and Odor:OPAQUE;REDDISH-BROWN LIQUID;AMMONICAL ODOR.

Percent Volatiles by Volume:50

Stability

Stability Indicator/Materials to Avoid:YES NOT KNOWN Stability Condition to Avoid:UNK

Disposal

Waste Disposal Methods: KEEP IN COVERED CONTAINERS PENDING DISPOSAL.SHIP WASTE MATL TO DISPOSL FACILTY IAW DOT/EPA REGS.HANDLE/DISPOSE IN FULL COMPLIANCE W/ALL INTNL, FED, STATE/LOCAL REGS; MFGR RECOMMENDS, FLUSH TO SEWER W/LG A MT OF WATER IAW FED, STATE/LOCAL EFFLUENT LAWS.



Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.