

122 5572,EKTAPRINT 2 DEVELOPER,PART D

MSDS Number

BCBTG

National Stock Number

6750-00K000922

Product Name

122 5572,EKTAPRINT 2 DEVELOPER,PART D

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID:122 5572,EKTAPRINT 2 DEVELOPER,PART D

MSDS Date:01/01/1985

FSC:6750

NIIN:00K000922

MSDS Number: BCBTG

Responsible Party

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

POTASSIUM CARBONATE; CAS# 584-08-7; WT% RANGE 40-45%

CAS: 584-08-7

RTECS: TS7750000

Fraction By Weight: 42.5%

POTASSIUM HYDROXIDE (SARA III)

CAS: 1310-58-3

RTECS: TT2100000

Fraction By Weight: 3 - 8%

OSHA PELC, 2 MG/M3

ACGIH TLV: C 2 MG/M3; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED COMPONENTS;WT%

Fraction By Weight: 54.5%

Hazards

Effects of Overexposure:EYES:BURNS:SKIN:PROLONGED OR REPEAT
CONTACT:IRRITANT,BURNS:INGEST:PAIN,VOMIT;INHALE:SHORT BREATH

First Aid

First Aid:EYES,SKIN,MUCOUS MEMBRANES:FLUSH W LG AMTS H*2O AT LEAST 15
MIN;INHALE:REMOVE TO FRESH AIR,KEEP CALM;INGEST:RINSE MOUTH;GET
MEDICAL ATTENTION FOR EYES,INGEST,OR BURNS-ADVISE PHYSICIAN THAT
PRODUCT IS CAUSTIC SOLUTION,TREAT ACCORDINGLY.

Fire Fighting

Extinguishing Media:NOT COMBUSTIBLE:USE MEDIA SUITABLE FOR ADJACENT
FIRE.

Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP;H*2O SPRAY COOL
CONT.

Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE IN HEAT OF FIRE.

Accidental Release

Spill Release Procedures:DO NOT TOUCH SPILLED MATERIAL.WEAR PROTECTIVE
EQUIPMENT.STOP LEAK IF POSSIBLE WITHOUT RISK.SM SP:ABSORB W
COMMERCIAL ABSORBENT & PUT IN APPR CONTAINERS.LG SP:CONTAIN W DIKE
& TRANSFER TO APPR CONTAINERS.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW
FIRE RISK AREA.PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL
CONTACT.KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:AVOID PROLONGED OR REPEATED CONTACT W CHEMICAL.REMOVE
& WASH CONTAMINATED CLOTHING.DISCARD CONTAMINATED SHOES.MAINTAIN
STRICT HYGIENE.STORE AWAY FROM STRONG MINERAL ACIDS.

Exposure Controls

Respiratory Protection:NO SPECIAL REQUIREMENTS

Ventilation:MECHANICAL(GEN./LOCAL EXHAUST) AS NECESSARY TO CONTROL MIST

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:NORMAL FULL WORK CLOTHING COVERING

ARMS,LEGS;NO SKIN CONTACT

Supplemental Safety and Health

MSDS FROM MFG DATED:78033:PART D OF FOUR PART PRODUCT,SAME STOCK

NUMBER.MSDS REISSUED 80121;PH APPROX 12.KEY1:C4.

Chemical Properties

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:17

Vapor Density:0.6

Spec Gravity:1.49

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR,COLORLESS AQUEOUS SOLUTION;ODORLESS.

Percent Volatiles by Volume:53

Stability

Stability Indicator/Materials to Avoid:YES

AVOID STRONG MINERAL ACIDS

Stability Condition to Avoid:MIST GENERATING CONDITIONS

Hazardous Decomposition Products:EXPECT CO*2, PER MFG.

Disposal

Waste Disposal Methods:DISPOSE IN FULL ACCORD WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE,& LOCAL REGULATIONS.MFG SUGGESTS

NEUTRALIZE WITH SODIUM BISULFATE & FLUSH TO SEWER WITH EXCESS WATER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.