

## **121 6241,EKTAPRINT 2 DEVEL REPLNSHR, PART A**

### **MSDS Number**

BCBTK

### **National Stock Number**

6750-00K000925

### **Product Name**

121 6241,EKTAPRINT 2 DEVEL REPLNSHR, PART A

### **Manufacturer**

EASTMAN KODAK COMPANY

### **Product Identification**

Product ID:121 6241,EKTAPRINT 2 DEVEL REPLNSHR, PART A

MSDS Date:05/01/1978

FSC:6750

NIIN:00K000925

MSDS Number: BCBTK

### **Responsible Party**

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

Emergency Phone: 716-722-5151

Info Phone: LOCAL MARKETING & DISTRIBUTION CTR.

Cage: 19139

### **Contractor**

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

### **Ingredients**

BENZYL ALCOHOL; CAS# 100-51-6; WT% RANGE 30-35%

CAS: 100-51-6

RTECS: DN3150000

Fraction By Weight: 32.5%

AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED COMPONENTS;WT%

Fraction By Weight: 67.5%

### **Hazards**

Effects of Overexposure:INHALE:IRRITNT;EYES:IRRITNT;SKIN:PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

### **First Aid**

First Aid:INHALE:REMOVE TO FRESH AIR,GIVE CPR/O\*2 IF NEED;EYES:FLUSH W LG AMTS H\*20 FOR 15 MIN;SKIN:FLUSH W LG AMTS H\*20;INGEST:RINSE MOUTH;GET IMMEDIATE MEDICAL ATTENTION FOR EYES OR INGEST.

### **Fire Fighting**

Extinguishing Media:SUITABLE FOR SURROUNDING FIRE:H\*2O SPRAY,CO\*2.  
Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP;H\*2O SPRAY COOL  
CONT.  
Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE IN HEAT OF FIRE.

## Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.STOP LEAK.H\*2O  
SPRAY HOT CONTAINERS.ABSORB WITH COMMERCIAL ABSORBENT,SHOVEL INTO  
WASTE DISPOSAL CONTAINERS;LG SPILL:DIKE WITH COMMERCIAL  
ABSORBENT,TRANSFER INTO WASTE DISP OSAL CONTAINERS.

## Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED  
AREA;PROTECT FROM PHYSICAL DAMAGE & AVOID SKIN CONTACT.KEEP  
CONTAINERS TIGHTLY CLOSED.  
Other Precautions:REMOVE & WASH CONTAMINATED CLOTHING.MAINTAIN STRICT  
HYGIENE.

## Exposure Controls

Respiratory Protection:WEAR APPROVED ORGANIC VAPOR RESPIRATOR,IF  
VENTILATION IS INADEQUATE  
Ventilation:ADEQUATE TO ELIMINATE MISTS:MECHANICAL(GEN/LOCAL EXHAUST)  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY/CHEM GOGGLES.  
Other Protective Equipment:FULL WORK CLOTHING;FACE SHIELD WHEN  
USING/MIXING PRODUCT.  
Supplemental Safety and Health  
MSDS FROM MFG DATED 5/1/78,REISSUED 5/78;PRODUCT FORMULATION CHANGED  
APPROX 5/80;PART A OF THREE PART PRODUCT.PH IS APPROX 8.0.PARTS B,C  
UNDER 6750-00-K00-1106,P/N A,B.

## Chemical Properties

HCC:N1  
Boiling Pt:B.P. Text:>212F,>100C  
Vapor Pres:16  
Vapor Density:2.5  
Spec Gravity:1.08  
Solubility in Water:COMPLETE  
Appearance and Odor:AMBER AQUEOUS SOLUTION,AMINE ODOR.  
Percent Volatiles by Volume:96

## Stability

Stability Indicator/Materials to Avoid:YES  
NONE NOTED  
Stability Condition to Avoid:NONE NOTED  
Hazardous Decomposition Products:EXPECT ORGANIC COMBUSTION  
PRODUCT:CO,CO\*2.

## Disposal

Waste Disposal Methods:KEEP IN COVERED CONTAINERS,PENDING  
DISPOSAL.HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE  
INTERNATIONAL,FEDERAL,STATE,& LOCAL REGULATIONS.MFG SUGGESTS SMALL  
QUANTITIES MAY BE FLUSHED W LARGE AMOUNTS OF WATER TO SEWER.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.