

## **198 6744,EKTAPRINT 3 BLEACH-FIX REGENERATOR**

### **MSDS Number**

BCBTQ

### **National Stock Number**

6750-00K000930

### **Product Name**

198 6744,EKTAPRINT 3 BLEACH-FIX REGENERATOR

### **Manufacturer**

EASTMAN KODAK COMPANY

### **Product Identification**

Product ID:198 6744,EKTAPRINT 3 BLEACH-FIX REGENERATOR

MSDS Date:01/01/1985

FSC:6750

NIIN:00K000930

MSDS Number: BCBTQ

### **Responsible Party**

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

### **Contractor**

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

### **Ingredients**

ETHYLENEDIAMINE-TETRAACETIC ACID (EDTA) (SARA III)

CAS: 60-00-4

RTECS: AH4025000

Fraction By Weight: 12.5%

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

THIO COMPOUND (TYPE NOT SPECIFIED)

Fraction By Weight: UNK

WATER (CAS #7732-18-5)

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: UNK

## Hazards

Effects of Overexposure:MSDS DATED 5/76 FM MFR STATES THAT EFFECTS OF OVEREXPOSURE ARE OF LOW HAZARD.

## First Aid

First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED ATTN;EYES:FLUSH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER FOR 15 MIN;PER MFR MSDS,"NONE APPEAR INDICAT ED"IN EMERGENCY/FIRST AID PROCEDURES.

## Fire Fighting

Flash Point:NONE  
Extinguishing Media:CO\*2,DRY CHEM  
Fire Fighting Procedures:USE SELF-CONTD BRTHG APP;COOL EXPSD CONT W/WATER SPRAY.  
Unusual Fire/Explosion Hazard:SPILL/RUNOFF MAY CAUSE POLLUTION,FIRE,AND/OR EXPLOSION HAZARD.

## Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.ELIM IGN SOURCES.USE PROTECTV CLOTHNG/SAFETY GLASSES.STOP LEAK W/O RISK.PROVIDE VENT.DIKE LG SPILL & PUMP INTO COVRD DRUMS;ABSORB/CONTAIN SM SPILL IN CONT;MFRG RECOMMENDS, FLUSH TO SEWER W.LG AMT OF WATER IAW EXISTING LAWS

## Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT;AVOID EXCESSIV HEAT  
Other Precautions:AVOID PROLONGED/REPEATED CONACT W/PRODUCT.REMOVE & WASH CONTAMINATED CLOTHING.WASH HANDS AFTER USE;APPROXIMATEL PRODUCT PH IS 5.5

## Exposure Controls

Respiratory Protection:NONE REQD IN NORMAL CONDITIONS.  
Ventilation:MECHANICAL(GEN)IF NEEDED  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES  
Other Protective Equipment:AS NEEDED BY LOCAL AUTHORITIES.  
Supplemental Safety and Health  
MSDS FM MFR DTD:5/75;ODOR OF SULFUR DIOXIDE FM PROD IS DUE TO THIO COMPD IN IT;FURTHERMORE,MFR INDICATED ON 3/22/83,CAT #198 6744-SIZE 75GAL HAS BEEN DISCONTD(DATE UNKNOWN)

## Chemical Properties

HCC:C3  
Boiling Pt:B.P. Text:>212F(100C)  
Vapor Pres:17  
Vapor Density:0.6  
Spec Gravity:1.20  
Solubility in Water:COMPLETE  
Appearance and Odor:SULFUR DIOXIDE ODOR;CLEAR & COLORLESS LIQUID.  
Percent Volatiles by Volume:60%

## Stability

Stability Indicator/Materials to Avoid:YES  
AVOID MINERAL ACIDS,OXIDIZERS/FLAMM MATL,ETC  
Stability Condition to Avoid:UNK  
Hazardous Decomposition Products:SULFUR DIOXIDE,NITROGEN,AMMONIA ETC

## Disposal

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.SHIP WASTE MATL TO DISPOSAL FACILTY IAW DOT/EPA REGS.HANDLE/DISPOSE IN FULL COMPLIANCE W/ALL INTNL,FED,STATE/LOCAL REGS;MFRG

RECOMMENDS,FLUSH TO SEWER W/LG AMT OF WATER IAW FED,STATE/LOCAL  
EFFLUENT LAWS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.