

## **162 5201,EKTAPRINT 3 DEVELOPER,PART B**

### **MSDS Number**

BCBVH

### **National Stock Number**

6750-00K000937

### **Product Name**

162 5201,EKTAPRINT 3 DEVELOPER,PART B

### **Manufacturer**

EASTMAN KODAK COMPANY

### **Product Identification**

Product ID:162 5201,EKTAPRINT 3 DEVELOPER,PART B

MSDS Date:01/01/1985

FSC:6750

NIIN:00K000937

MSDS Number: BCBVH

### **Responsible Party**

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

### **Contractor**

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

### **Ingredients**

POTASSIUM CARBONATE(35-40%) (CAS #584-08-7)

CAS: 584-08-7

RTECS: TS7750000

Fraction By Weight: 37.5%

ACGIH TLV: 2MG/CUM(AS KOH)

AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED

Fraction By Weight: 62.5%

### **Hazards**

Effects of Overexposure:EYES:MAY CAUSE BURNS;SKIN:MAY CAUSE IRRITATION.

### **First Aid**

First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED  
ATTN;EYES:FLUSH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED

HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER FOR 15 MIN.FOR IRRIT,GET MED ATTN.

## Fire Fighting

Flash Point:NONE

Extinguishing Media:CO\*2,DRY CHEM

Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPSD CONT W/WATER SPRAY.

Unusual Fire/Explosion Hazard:NONE KNOWN

## Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS,PROVIDE VENTILATION/SAFETY EQUIPMENTS IF NECESSARY.DIKE LG SPILL & PUMP INTO COVERED CONTNRS;ABSORB SM SPILL W/ABSORBING MATL & PLACE IN SAME CONTNR;MFR SUGGESTS FLUSH DO WN TO SEWER W/LG AMT OF H\*2O IAW EXISTING REGS.

## Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.KEEP AWAY FROM ACIDS.

Other Precautions:AVOID PROLONGED/REPEATED CONTACT W/PRODUCT.REMOVE & WASH CONTAMINATED CLOTHING.WASH HANDS AFTER USE.APPROX PH OF PRODUCT:12.0

## Exposure Controls

Respiratory Protection:NONE REQD IN NORMAL CONDITIONS.

Ventilation:MECHANICAL(GEN)IF NEEDED

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:AS NEEDED BY LOCAL AUTHORITIES.

Supplemental Safety and Health

MSDS FM MFR DATE:10-21-75;PER MFR,ITEM DISCONTD APPROX 1979:THIS DATA FOR PART B OF 3 PART PRODUCT;POT CARBONATE DISSOCIATES IN SOLN TO GIVE POT HYDROXIDE(PH APPROX 12 OF PROD SOLN).

## Chemical Properties

HCC:B3

Boiling Pt:B.P. Text:>212F

Vapor Pres:17

Vapor Density:0.6

Spec Gravity:1.49

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR SOLUTION,ODORLESS

Percent Volatiles by Volume:56%

## Stability

Stability Indicator/Materials to Avoid:YES

PER MFR AVOID FROM MINERA ACIDS

Hazardous Decomposition Products:SULFUR DIOXIDE

## Disposal

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.DISPOSE IN FULL COMPLIANCE W/FEDERAL,STATE & LOCAL REGULATIONS;MFR RECOMMENDS TO FLUSH DWN TO SEWER W COPIOUS AMT H\*2O.STATE & LOCAL EFFLUENT LAWS TAKE PREC EDENCE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.