

## **162 5201,EKTAPRINT 3 DEVELOPER,PART C**

### **MSDS Number**

BCBVJ

### **National Stock Number**

6750-00K000937

### **Product Name**

162 5201,EKTAPRINT 3 DEVELOPER,PART C

### **Manufacturer**

EASTMAN KODAK COMPANY

### **Product Identification**

Product ID:162 5201,EKTAPRINT 3 DEVELOPER,PART C

MSDS Date:01/01/1985

FSC:6750

NIIN:00K000937

MSDS Number: BCBVJ

### **Responsible Party**

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

### **Contractor**

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

### **Ingredients**

4-AMINO-N-ETHYL-N-(B-METHANESULFONAMIDOETHYL)-M-TOLUIDINE

Fraction By Weight: 22.5%

ACGIH TLV: 5 PPM (AS SO\*2)

AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED

Fraction By Weight: 77.5%

### **Hazards**

Effects of Overexposure:INH:SO\*2 CAUSES IRRIT;EYES:SO\*2/LIQ CAUSES IRRIT;SKIN:LIQ CONTCT CAUSES IRRIT.MAY CAUSE ALLERGY ACTN

### **First Aid**

First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED ATTN;EYES:FLUSH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER FOR 15 MIN.FOR IRRIT GET MED ATTN.

## Fire Fighting

Flash Point:NONE  
Extinguishing Media:CO\*2,DRY CHEM  
Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPSD CONT W/WATER SPRAY.  
Unusual Fire/Explosion Hazard:NONE KNOWN

## Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS,PROVIDE VENTILATION/SAFETY EQUIPMENTS IF NECESSARY. DIKE LG SPILL & PUMP INTO COVERED CONTNRS;ABSORB SM SPILL W/ABSORBING MATL & PLACE IN SAME CONTNR;MFR SUGGESTS FLUSH DO WN TO SEWER W/LG AMT OF H\*2O IAW EXISTING REGS.

## Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.  
Other Precautions:AVOID PROLONGED/REPEATED CONTACT W/PRODUCT.ROUTINE USE OF A NON-ALKALINE(ACID)TYPE HAND CLEANER WILL HELP MINIMIZE OF ALLERGIC SKIN REACTION;APPROX PRODUCT PH:1.0

## Exposure Controls

Respiratory Protection:NONE REQD IN NORMAL CONDITIONS.  
Ventilation:MECHANICAL(GEN) IF NEEDED  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES  
Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT.  
Supplemental Safety and Health  
MSDS FM FMR DATE:10-21-75;PER MFR,ITEM DISCONTD APPROX 1979;THIS DATA FOR PART C OF 3 PART PRODUCT;PROD DISSOCIATES TO H\*2O\*4 IN SOLN,C2 STG CODE ASSIGNED;UNIT CONT QTY YIELDS 3.5 GAL SOLN.

## Chemical Properties

HCC:C3  
Boiling Pt:B.P. Text:>212F/>100C  
Vapor Pres:17  
Vapor Density:0.6  
Spec Gravity:1.19  
Solubility in Water:COMPLETE  
Appearance and Odor:PUNGENT SULFUR DIOXIDE ODOR,AMBER COLOR LIQ  
Percent Volatiles by Volume:65%

## Stability

Stability Indicator/Materials to Avoid:YES  
PER MFR AVOID FROM MINERA ACIDS & STRONG ALKALI  
Hazardous Decomposition Products:SULFUR DIOXIDE

## Disposal

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.DISPOSE IN FULL COMPLIANCE W/FEDERAL,STATE & LOCAL REGULATIONS;MFR RECOMMENDS TO FLUSH DOWN TO SEWER W COPIOUS AMT H\*2O.STATE & LOCAL EFFLUENT LAWS TAKE PRE CEDENCE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.