

## **189 0649,EKTAPRINT 3 STBLZR & REPL**

### **MSDS Number**

BCBVL

### **National Stock Number**

6750-00K000939

### **Product Name**

189 0649,EKTAPRINT 3 STBLZR & REPL

### **Manufacturer**

EASTMAN KODAK COMPANY

### **Product Identification**

Product ID:189 0649,EKTAPRINT 3 STBLZR & REPL

MSDS Date:01/01/1985

FSC:6750

NIIN:00K000939

MSDS Number: BCBVL

### **Responsible Party**

EASTMAN KODAK COMPANY

Emergency Phone: 716-722-5151

Cage: 19139

### **Contractor**

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

### **Ingredients**

NON HAZARDOUS INGREDIENTS

Fraction By Weight: 86.5%

ACETIC ACID (SARA III)

CAS: 64-19-7

RTECS: AF1225000

Fraction By Weight: 13.5%

OSHA PEL10 PPM

ACGIH TLV: 10 PPM/15 STEL; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

### **Hazards**

Effects of Overexposure:CONTACT WITH SKIN/EYES MAY IRRITAT.VAPOR IRRITATING. NO CHRONIC EXPOSURE EFFECTS ANTICIPATED.

### **First Aid**

First Aid:EYES:IRRIGATE WITH WATER 15 MIN.SKIN:WASH WITHSOAP AND WATER.INHALED:REMOVE TO FRESH AIR.GET MEDICAL ATTENTION.

## Fire Fighting

Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP;PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:CONTAINER MAY EXPLODE IN HEAT OF  
FIRE.VAPORS MAY EXPLODE.

## Accidental Release

Spill Release Procedures:ELIMINATE IGNITION SOURCES.EVACUTE UNPROTECTED  
PERSONS.NEUTRALIZE WITH SODIUM BESULFITE.ABSORB WITH RAGS OR  
COMMERCIAL ABSORBENT.LG SPILL:DIKE,NEUTRALIZE WITH SODIUM  
BISULFITE.PUMP TO SALVAGE TANK/DRU M.

## Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL-VENTED LOW FIRE  
RISK AREA.PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED.AVOID  
STRONG ALKALI.  
Other Precautions:NONE.

## Exposure Controls

Respiratory Protection:WEAR CHEM CARTRIDGE RESPIRATOR IF NEEDED.CONTROL  
VAPORWITH EXHAUST.  
Ventilation:MECHANICAL(GENERAL)/LOCAL EXHAUST IF NEEDED  
Protective Gloves:RUBBER  
Eye Protection:SAFETY/CHEMICAL GOGGLES  
Other Protective Equipment:NORMAL WORK CLOTHING TO PREVENT REPEATED  
SKIN CONTACT.  
Supplemental Safety and Health

## Chemical Properties

HCC:N1  
Boiling Pt:B.P. Text:>212F/100C  
Vapor Pres:30  
Vapor Density:0.9  
Spec Gravity:1.08  
Solubility in Water:COMPLETE  
Appearance and Odor:CLEAR-VINEGAR ODOR  
Percent Volatiles by Volume:95

## Stability

Stability Indicator/Materials to Avoid:YES  
AVOID STRONG ALKALI.  
Hazardous Decomposition Products:AMMONIA,CO\*2,CO.

## Disposal

Waste Disposal Methods:NEUTRALIZE WITH SODIUM BISULFITE.FLUSH TO SEWER  
WITH COPIOUS AMTS OF WATER OR DISSOLVE IN COMBUSTIBLE SOLVENT,THEN  
SPRAY INTOINCINERATOR WITH AFTERBURNER AND SCRUBBER.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.