

180 5456, FLEXICOLOR DEVELOPER REPL, PART A

MSDS Number

BCBWM

National Stock Number

6750-00K000959

Product Name

180 5456, FLEXICOLOR DEVELOPER REPL, PART A

Manufacturer

EASTMAN KODAK CO

Product Identification

Product ID:180 5456,FLEXICOLOR DEVELOPER REPL,PART A

MSDS Date:01/01/1985

FSC:6750

NIIN:00K000959 MSDS Number: BCBWM

Responsible Party

EASTMAN KODAK CO.

343 STATE ST.

ROCHESTER, NY 14650

Emergency Phone: 716-772-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

WATER(55-60%)(CAS #7732-18-5)

CAS: 7732-18-5 RTECS: ZC0110000

Fraction By Weight: 60%

POTASSIUM CARBONATE(35-40%) (CAS #584-08-7)

CAS: 584-08-7

RTECS: TS7750000

Fraction By Weight: 40%

Hazards

Effects of Overexposure:LOW HAZARD

First Aid

First Aid: NONE INDICATED BY MANUFACTURER, BUT GOOD INDUSTRIAL HYGIENE PRACTICES SHOULD BE FOLLOWED.

Fire Fighting



Fire Fighting Procedures: NONE Unusual Fire/Explosion Hazard: NONE

Accidental Release

Spill Release Procedures: ELIMINATE IGNITION SOURCES. NEUTRALIZE WITH BISULFATE. FLUSH TO SEWER WITH COPIUS AMOUNTS OF WATER. FEDERAL, STATE AND LOCAL EFFLUENT LAWS TAKE PRECEDENCE.

Handling

Handling and Storage Precautions: AVOID CONTACT WITH MINERAL ACIDS.KEEP CONTAINERS CLOSED.PROTECT FROM PHYSICAL DAMAGE.STORE IN COOL, DRY PLACE.

Other Precautions: NONE

Exposure Controls

Respiratory Protection: NONE NORMALLY REQUIRED

Ventilation:MECHANICAL(GENERAL)
Protective Gloves:IMPERVIOUS

Eye Protection: CHEMICAL/SAFETY GOGGLES

Supplemental Safety and Health

PH IS APPROXIMATELY 11.2 THIS ITEM HAS BEEN DISCONTINUED BY EASTMAN

KODAK.

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:>212F/100C

Vapor Pres:17 Vapor Density:0.6 Spec Gravity:1.41

Solubility in Water: COMPLETE

Appearance and Odor: CLEAR SOLUTION, ODORLESS.

Percent Volatiles by Volume:62

Stability

Stability Indicator/Materials to Avoid:YES MINERAL ACIDS

Hazardous Decomposition Products: SULFUR DIOXIDE

Disposal

Waste Disposal Methods: NEUTRALIZE WITH BISULFATE.FLUSH TO SEWER WITH COPIUS AMOUNTS OF WATER.FEDERAL, STATE AND LOCAL EFFLUENT LAWS TAKE PRECEDENCE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.