# **ITEK CAMERA/PROCESSOR FIXER**

### **MSDS Number**

**BCBYC** 

#### **National Stock Number**

6750-00K000983

#### **Product Name**

ITEK CAMERA/PROCESSOR FIXER

#### Manufacturer

EASTMAN KODAK COMPANY

#### **Product Identification**

Product ID:ITEK CAMERA/PROCESSOR FIXER MSDS Date:01/01/1985 FSC:6750 NIIN:00K000983

# MSDS Number: BCBYC **Responsible Party**

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER, NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

# **Contractor**

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

#### **Ingredients**

AMMONIUM THIOSULFATE(15-20%) (CAS #7783-18-8)

CAS: 7783-18-8 RTECS: XN6465000

Fraction By Weight: 17.5%

AMMONIUM THIOCYANATE(10-15%) (CAS #1762-95-4)

RTECS: XX7875000

Fraction By Weight: 12.5%

ACETIC ACID (SARA III)

CAS: 64-19-7 RTECS: AF1225000

Fraction By Weight: 3.0%



OSHA PEL10 PPM

ACGIH TLV: 10 PPM/15 STEL; 9192 EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

WATER(65-70%) (CAS #7732-18-5)

CAS: 7732-18-5 RTECS: ZC0110000

Fraction By Weight: 67.0%

**Hazards** 

Effects of Overexposure: LOW HAZARD TO HEALTH

First Aid

First Aid: NONE APPEAR INDICATED, BUT GOOD SAFETY HYGIENE PRACTICES

SHOULD BE FOLLOWED.

#### **Accidental Release**

Spill Release Procedures: NEUTRALIZE WITH SODIUM CARBONATE.FLUSH DOWN SEWER WITH COPIOUS AMOUNTS OF WATER.FEDERAL, STATE AND LOCAL EFFLUENT LAWS TAKE PRECEDENCE.

### Handling

Handling and Storage Precautions:STORE AWAY FROM ALKALI STORE IN COOL,DRY,PLACE.KEEP CONTAINERS CLOSED.PROTECT FROM PHYSICAL

PROTECTION.

Other Precautions: NONE

## **Exposure Controls**

Respiratory Protection: NONE NORMALLY REQUIRED. Ventilation: MECHANICAL (GENERAL) RECOMMENDED

Protective Gloves: IMPERVIOUS

Eye Protection: CHEMICAL/SAFETY GOGGLES.

Other Protective Equipment: AS NECESSARY TO PREVENT CONTACT.

Supplemental Safety and Health

MSDS FM MFR DTD:3/18/82; PRODUCT MFD BY EASTMAN FOR ITEK CORP FOR RESALE

UNDER SOLUTION #4295,KODAK ACCESSION #365721;APPROX.PH:4.9; CAT #

NOT AVAILABLE

#### **Chemical Properties**

HCC:C3

Boiling Pt:B.P. Text:>212F/100C

Vapor Pres:32 Vapor Density:0.7

Spec Gravity: 1.16

Solubility in Water: COMPLETE

Appearance and Odor: CLEAR SOLUTION, SLIGHT VINEGAR ODOR, COLORLESS.

Percent Volatiles by Volume: 76

# Stability

Stability Indicator/Materials to Avoid:YES

AVOID ALKALI

Hazardous Decomposition Products: NONE

## Disposal

Waste Disposal Methods: NEUTRALIZE WITH SODIUM CARBONATE.FLUSH DOWN SEWER WITH COPIOUS AMOUNTS OF WATER.FEDERAL, STATE AND LOCAL EFFLUENT LAWS TAKE PRECEDENCE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department



of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.