

## **121 6712,KODALITH MP II DEVLPR REPL,PART B**

### **MSDS Number**

BCBYP

### **National Stock Number**

6750-00K000992

### **Product Name**

121 6712,KODALITH MP II DEVLPR REPL,PART B

### **Manufacturer**

EASTMAN KODAK COMPANY

### **Product Identification**

Product ID:121 6712,KODALITH MP II DEVLPR REPL,PART B

MSDS Date:01/11/1985

FSC:6750

NIIN:00K000992

Kit Part:Y

MSDS Number: BCBYP

### **Responsible Party**

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

US

Emergency Phone: 716-722-5151

Cage: 19139

### **Contractor**

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

### **Ingredients**

SODIUM FORMALDEHYDE BISULFITE

CAS: 870-72-4

RTECS: PB2200000

Fraction By Weight: 5-10%

OSHA PELNONE ESTABLISHED

ACGIH TLV: NONE ESTABLISHED

POTASSIUM METABORATE

CAS: 13709-94-9

Fraction By Weight: 1-5%

OSHA PEL1 MG/M3 BORATE

ACGIH TLV: 1 MG/M3 BORATE

WATER

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 25-30%

DIETHANOLAMINE (SARA III)

CAS: 111-42-2

RTECS: KL2975000

Fraction By Weight: 62%

OSHA PEL3 PPM

ACGIH TLV: 3 PPM; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

## Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:VAPOR MAY CAUSE UPPER RESPIRATORY TRACT IRRITATION IF ABOVE THE TLV.

Medical Cond Aggravated by Exposure:NONE STATED.

## First Aid

First Aid:INHALE:REMOVE TO FRESH AIR,TREAT SYMPTOMATICALLY; EYES:FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES; SKIN:FLUSH WITH LARGE AMOUNTS OF WATER.

## Fire Fighting

Flash Point:NONE

Extinguishing Media:USE SUITABLE MEDIA FOR SURROUNDING FIRE.

Fire Fighting Procedures:FIREFIGHTER SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CONTAINERS MAY EXPLODE IN HEAT OF FIRE.

## Accidental Release

Spill Release Procedures:FLUSH MATERIAL TO AN ACID-FREE SEWER WITH LARGE AMOUNTS OF WATER.

## Handling

Handling and Storage Precautions:KEEP FROM CONTACT WITH OXIDIZING MATERIALS. KEEP CONTAINER TIGHTLY CLOSED AND AWAY FROM STRONG ACIDS.

Other Precautions:AVOID PROLONGED OR REPEATED CONTACT W CHEMICAL.REMOVE & WASH CONTAMINATED CLOTHING.MAINTAIN STRICT HYGIENE.

## Exposure Controls

Respiratory Protection:NONE USUALLY.

Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES.

Other Protective Equipment:NORMAL FULL WORK CLOTHING COVERING

ARMS,LEGS:NO SKIN CONTACT

Supplemental Safety and Health

KEY1:N1. PART B OF TWO PART PRODUCT. PART A IS UNDER LSN

6750-00-K00-0990.

## Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:212,100C

Vapor Pres:15

Vapor Density:2.27  
Spec Gravity:1.15  
pH:11.8  
Solubility in Water:COMPLETE  
Appearance and Odor:CLEAR,YELLOW-GREEN/ORANGE AQUEOUS SOLN;FISHY ODOR  
Percent Volatiles by Volume:93

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS, STRONG ACIDS.  
Stability Condition to Avoid:NONE NOTED  
Hazardous Decomposition Products:NONE NOTED

## Disposal

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT  
TO FEDERAL, STATE, OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.