

## **177 0072,MICRO RESIST DEVELOPER**

### **MSDS Number**

BCBZC

### **National Stock Number**

6750-00K001003

### **Product Name**

177 0072,MICRO RESIST DEVELOPER

### **Manufacturer**

EASTMAN KODAK COMPANY

### **Product Identification**

Product ID:177 0072,MICRO RESIST DEVELOPER

MSDS Date:01/01/1985

FSC:6750

NIIN:00K001003

MSDS Number: BCBZC

### **Responsible Party**

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

### **Contractor**

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

### **Ingredients**

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: 97.5%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

NON-AQUEOUS SOLUTION,HAZARD UNKNOWN,WT% RANGE BY DIFFERENCE

Fraction By Weight: 2.5%

### **Hazards**

Effects of Overexposure:INHALE:IRRITNT;EYE:LIQUID

IRRITNT;SKIN:PROLONGED,REPEATED CONTACT MAY CAUSE IRRITATION.

### **First Aid**

First Aid: INHALE: REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF  
NEED; EYES/SKIN: FLUSH W LG AMTS H\*2O FOR 15 MIN; INGEST: RINSE  
MOUTH, DO NOT INDUCE VOMIT, GET IMMEDIATE MEDICAL ATTENTION; ANY  
OVEREXPOSURE: CALL PHYSICIAN.

## Fire Fighting

Flash Point: 110F, 43C TCC  
Lower Limits: 0.8  
Upper Limits: 5.0  
Extinguishing Media: CO\*2, DRY FOAM  
Fire Fighting Procedures: SELF-CNTND BRTHG APP; H\*2O SPRAY COOL CONT.  
Unusual Fire/Explosion Hazard: CONTAINERS MAY EXPLODE IN HEAT OF FIRE.

## Accidental Release

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. ELIM IGNITION  
SOURCES. PROVIDE VENTILATION. STOP LEAK. H\*2O SPRAY COOL CONT/DIVERT  
SPILL FROM FIRE/HEAT. ABSORB W COMMERCIAL ABSORBENT, SHOVEL INTO  
METAL DRUMS; LG SPILL: DIKE W COMMERCIAL ABSORBENT, PUMP INTO COVERED  
DRUMS.

## Handling

Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED, LOW  
FIRE RISK AREA. KEEP CONTAINERS TIGHTLY CLOSED. PROTECT FROM PHYSICAL  
DAMAGE.  
Other Precautions: MAINTAIN STRICT HYGIENE, AVOID PHYSICAL CONTACT, REMOVE  
& WASH CONTAMINATED CLOTHING.

## Exposure Controls

Respiratory Protection: FOR EXPOSURE: SELF-CNTND BRTH APP/APPR RESPIRATOR  
FOR ORGANIC SOLVENT  
Ventilation: MECHANICAL (GENERAL/LOCAL EXHAUST)  
Protective Gloves: IMPERVIOUS  
Eye Protection: SAFETY/CHEM GOGGLES  
Other Protective Equipment: FULL WORK CLOTHING.  
Supplemental Safety and Health  
MSDS FROM MFG DATED 77350, REISSUED 78001. PRODUCT IS STODDARD  
SOLVENT. BOILING PT RANGE: 160-194C

## Chemical Properties

Boiling Pt: B.P. Text: 320-381F  
Vapor Pres: Vapor Density: 4  
Spec Gravity: 0.790  
Solubility in Water: NEGLIGIBLE  
Appearance and Odor: COLORLESS SOLVENT, LIQUID MIX; PETROLEUM ODOR  
Percent Volatiles by Volume: 100

## Stability

Stability Indicator/Materials to Avoid: YES  
NONE NOTED  
Stability Condition to Avoid: IGNITION SOURCES  
Hazardous Decomposition Products: NONE NOTED

## Disposal

Waste Disposal Methods: KEEP IN COVERED CONTAINERS PENDING  
DISPOSAL. HANDLE AND DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE  
INTERNATIONAL, FEDERAL, STATE AND LOCAL REGULATIONS. MFG SUGGESTS  
BURNING AS ORGANIC SOLVENT.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.