

191 6733,MICRO RESIST RINSE

MSDS Number

BCBZG

National Stock Number

6750-00K001006

Product Name

191 6733,MICRO RESIST RINSE

Manufacturer

EASTNAM KODAK COMPANY

Product Identification

Product ID:191 6733,MICRO RESIST RINSE

MSDS Date:01/01/1985

FSC:6750

NIIN:00K001006

MSDS Number: BCBZG

Responsible Party

EASTNAM KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 5K871

Contractor

EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

ROCHESTER, NY 14650-3129

US

800-828-6203

Cage: 5K871

Ingredients

N-BUTYL ACETATE (SARA III)

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 97.5%

OSHA PEL150 PPM/200 STEL

ACGIH TLV: 150 PPM/200STEL;9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

NON-AQUEOUS SOLUTION,HAZARDUNKNOWN,UNIDENTIFIED(0-5%)

Fraction By Weight: 2.5%

Hazards

Effects of Overexposure:SKIN:REPTD/PROLNGD LIQ CONTCT CAUSES

DEFATTNG;EYES:PROLNGD EXPOSr TO VAP CAUSES IRRIT*SEE SUPP DATA*

First Aid

First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED
ATTN;EYES:FLUSH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED
HELP;SKIN:FLUSH IMMED W/PLENty OF WATER FOR 15 MIN.FOR IRRIT GET
MED ATTN.

Fire Fighting

Flash Point:82F(28C)-TCC
Lower Limits:1.3%
Upper Limits:7.6%
Extinguishing Media:CO*2,DRY CHEM,DRY FOAM
Fire Fighting Procedures:USE SELF-CNTND BRTHG APP;COOL EXPSD CONT
W/WATER SPRAY.
Unusual Fire/Explosion Hazard:SPILL/RUNOFF MAY CAUSE
POLLUTION,FIRE/EXPLOSION HAZARD;CONTNRS(EMPTY/FULL)MAY EXPLODE IN
HEAT OF FIR

Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.ELIM IGN
SOURCES.USE PROTCTV/SAFETY EQUIP.STOP LEAK W/O RISK.PROVIDE
VENT.DIKE LG SPILL.PUMP LIQ TO SALVAGE TANK.ABSORB REMAINING LIQ
W/ABSRBNG MATL & SHOVEL INTO DRUMS;PE R MFR SOAK UP SM SPILL
W/ABSRBNT MATL IAW REGS.

Handling

Handling and Storage Precautions:STORE AWAY FROM STRONG ALKALI.STORE IN
COOL,DRY PLACE.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM
PHYSICAL DAMAGE.
Other Precautions:AVOID SKIN/EYE CONTACT W/CHEMICAL PRODUCT.WASH
THOROUGHLY AFTER HANDLING.

Exposure Controls

Respiratory Protection:AN APPROVD ORGANIC VAP RESPIRATOR FOR EMERGENCY
USE ONLY
Ventilation:LOCAL EXHAUST & MECHANICAL(GENERAL)RECOMMENDED BY MFR
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES/GOGGLS
Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT
Supplemental Safety and Health
*INHALATION EFFECT:PROLNGD EXPOSr TO HIGH VAP CONC MAY CAUSE ANESTHETIC
W/HEADACHE,DIZZ & NAUSEA;MSDS FM MFR DTD :3/4/77

Chemical Properties

Boiling Pt:B.P. Text:255-259F
Vapor Pres:11
Vapor Density:4.01
Spec Gravity:0.895
Solubility in Water:NEGLIGIBLE
Appearance and Odor:COLORLESS LIQUID,FRUITY ODOR
Percent Volatiles by Volume:100

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZING & CORROSIVE MATERIAL.
Stability Condition to Avoid:SOURCE OF IGNITION
Hazardous Decomposition Products:BURNING MAY RESULT IN EVOLUTION OF CO
& CO*2

Disposal

Waste Disposal Methods:KEEP IN COVERED CONTNRS PENDING DISPOSAL.SHIP
WASTE MATL IAW DOT TO DISPOSAL/INCINERATING FACILITY.HANDLE/DISPOSE
IN FULL COMPLIANCE W/ALL FED,STATE/LOCAL REGS;MFR
RECOMMENDS:BURN-TREAT AS ORGANIC SOL VNts.FED,ST.& LOCAL EFFLUENT
LAWS TAKE PRECEDENCE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.