

198 9938,MICRO RESIST THINNER

MSDS Number

BCBZM

National Stock Number

6750-00K001011

Product Name

198 9938,MICRO RESIST THINNER

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID:198 9938,MICRO RESIST THINNER

MSDS Date:01/01/1985

FSC:6750

NIIN:00K001011

MSDS Number: BCBZM

Responsible Party

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 92.5%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

NON-AQUEOUS SOLUTION, HAZARD UNKNOWN, UNIDENTIFIED (5-10%)

Fraction By Weight: 7.5%

Hazards

Effects of Overexposure:SKIN:REPTD/PROLNGD LIQ CONTCT CAUSES

DEFATTNG;EYES:CONTACTW/LIQUID CAUSES IRRITATION*SEE SUPP DATA*

First Aid

First Aid:INH:REMOVE FROM EXPOSURE. GIVE CPR/OXY IF NEEDED & GET MED
ATTN; EYES:FLUSH IMMED W/ WATER FOR AT LEAST 15 MIN. GET MED HELP;
SKIN:FLUSH IMMED W/PLENTY OF WATER FOR 15 MIN. FOR IRRIT GET
MEDATTN.

Fire Fighting

Flash Point:84F (29C)-TCC
Lower Limits:1.0%
Upper Limits:6.0%
Extinguishing Media:CO*2,DRY CHEM, DRY FOAM
Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPSD CONT
W/WATER SPRAY.
Unusual Fire/Explosion Hazard:SPILL/RUNOFF MAY CAUSE
POLLUTION,FIRE/EXPLOSION HAZARD;CONTNRS(EMPTY/FULL)MAY EXPLDE IN
HEAT OF FIRE

Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.ELIM IGN
SOURCES.USE PROTCTV/SAFETY EQUIP.STOP LEAK W/O RISK.PROVIDE
VENT.DIKE LG SPILL.PUMP LIQ TOSALVAGE TANK.ABSORB REMAINING LIQ
W/ABSRBNG MATL & SHOVEL INTO DRUMS;PER MFR SOAK UP SM SPILL
W/ABSRBNT MATL IAWREGS.

Handling

Handling and Storage Precautions:STORE AWAY FROM SOURCE OF IGN.STORE IN
COOL,DRY PLACE.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM
PHYSICALDAMAGE.

Exposure Controls

Respiratory Protection:AN APPRVD ORGANIC VAP RESPIRATOR FOR EMERGENCY
USE ONLY
Ventilation:LOCAL EXHAUST & MECHANICAL(GENERAL) RECOMMENDED BY MFGR.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES/GOGGLES
Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT.
Supplemental Safety and Health
*INHALATION EFFECT:PROLONGED EXPOSURE TO HIGH VAP CONC MAY CAUSE
ANESTHETIC EFFECT ALONG WITH HEADACHES, DIZZ & NAUSEA; MSDS FM MFR
DTD:5/8/78.

Chemical Properties

HCC:F3
Boiling Pt:B.P. Text:285 F(140C)
Vapor Pres:5
Vapor Density:3.6
Spec Gravity:0.890
Solubility in Water:NEGLIGIBLE
Appearance and Odor:COLORLESS LIQUID-PETROLEUM ODOR
Percent Volatiles by Volume:95%

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZING & CORROSIVE MATERIAL
Stability Condition to Avoid:SOURCE OF IGNITION
Hazardous Decomposition Products:BURNING MAY RESULT IN EVOLUTION OF CO
& CO*2.

Disposal

Waste Disposal Methods:KEEP IN COVERED CONTNRS PENDING DISPOSAL.SHIP
WASTE MATL IAW DOT TO DISPOSAL/INCINERATING FACILITY.HANDLE/DISPOSE
IN FULL COMPLIANCE W/ALL FED,STATE/LOCAL REGS;MFR
RECOMMENDS:BURN-TREAT AS ORGANIC SOL VNTS.FED,ST.& LOCAL EFFLUENT
LAWS TAKE PRECEDENCE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.