

## **167 0835,PHOTO RSIST THNNR FOR PHOTOENGRAVG**

### **MSDS Number**

BCCBZ

### **National Stock Number**

6750-00K001041

### **Product Name**

167 0835,PHOTO RSIST THNNR FOR PHOTOENGRAVG

### **Manufacturer**

EASTMAN KODAK COMPANY

### **Product Identification**

Product ID:167 0835,PHOTO RSIST THNNR FOR PHOTOENGRAVG

MSDS Date:01/01/1985

FSC:6750

NIIN:00K001041

MSDS Number: BCCBZ

### **Responsible Party**

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

### **Contractor**

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

### **Ingredients**

2-METHOXYETHYL ACETATE (EGMEA)

CAS: 110-49-6

RTECS: KL5950000

Fraction By Weight: 96.5%

OSHA PELS, 25 PPM

ACGIH TLV: S, 5 PPM; 9192

NON-AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED (2-5%)

Fraction By Weight: 3.5%

### **Hazards**

Effects of Overexposure:EYES:LIQ CONTCT MAY  
IRRITATE;SKIN:PROLNGD/REPEATD CONTCT MAY CAUSE IRRIT.MAY BE \*SEE  
SUPPL DATA\*

## First Aid

First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED ATTN;EYES:FLUSH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER OFR 15 MIN.FOR BURNS GET MED ATTN.

## Fire Fighting

Flash Point:120F(49C)-TCC  
Lower Limits:1.7  
Upper Limits:8.2  
Extinguishing Media:CO\*2,DRY CHEM,DRY FOAM  
Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPSD CONT W/WATER SPRAY.  
Unusual Fire/Explosion Hazard:RUNOFF/SPILL MAY CAUSE POLLUTION/FIRE HAZARD

## Accidental Release

Spill Release Procedures:ELIM IGN SOURCES.EVACUATE UNPROTECTED PERSONS.MFR STATE:HAVE GOOD VENTILATION-USE RESPIRATOR.CLEAN W/ABSORPTIVE-SAWDUST,RAGS,ETC.FLUSH WELL W/H\*20.STATE/LOCAL LAWS TAKE PRECEDENCE;LG SPILL:DIKE LIQ & PUMP TO SALVAGE TANK PENDING DISPOSAL

## Handling

Handling and Storage Precautions:STORE AWAY FROM STRONG ALKALI STORE IN COOL,DRY PLACE.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.  
Other Precautions:AVOID SKIN/EYE CONTACT W/CHEMICAL PRODUCTS.WASH THOROUGHLY AFTER HANDLING.

## Exposure Controls

Respiratory Protection:AN APPRVD ORGANIC VAP RESPIRATOR FOR EMERGENCY USE ONLY  
Ventilation:LOCAL EXHAUST & MECHANICAL(GENERAL) RECOMMENDED BY MFR.  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES/GOGGLES  
Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT.  
Supplemental Safety and Health  
OVEREXPOSURE EFFECTS:ABSORBED THROUGH THE INTACT SKIN;INH:REPEATD/PROLNGD EXPOSURE TO HIGH CONC MAY RESULT IN CHANGES IN THE BLOOD PICTURE & POSSIBLE KIDNEY DAMAGE;MSDS FM MFR DTD:11-14-77

## Chemical Properties

HCC:F4  
Boiling Pt:B.P. Text:282-291F  
Vapor Pres:3.3  
Vapor Density:4.1  
Spec Gravity:1.005  
Solubility in Water:COMPLETE  
Appearance and Odor:COLORLESS LIQUID-AROMATIC ODOR  
Percent Volatiles by Volume:98%

## Stability

Stability Indicator/Materials to Avoid:YES  
NONE PER MFR.  
Stability Condition to Avoid:SOURCE OF IGNITION  
Hazardous Decomposition Products:BURNING MAY RESULT IN THE EVOLUTION OF CO & CO\*2.

## Disposal

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.COMPLY W/ALL APPLICABLE FED,STATE/LOCAL REGS REGARDING DISPOSAL;MFR SUGGESTS CONTROLLED BURNING METHOD OF DISPOSAL IAW FEDERAL,STATE & LOCAL EFFLUENT LAWS CONCERNING DISPOSAL PROCEDURES/METHODS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.