

195 6853,PHOTO RESIST THNNR FOR LITHOGRAPHY

MSDS Number

BCCCD

National Stock Number

6750-00K001044

Product Name

195 6853,PHOTO RESIST THNNR FOR LITHOGRAPHY

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID:195 6853,PHOTO RESIST THNNR FOR LITHOGRAPHY

MSDS Date:01/01/1985

FSC:6750

NIIN:00K001044

MSDS Number: BCCCD

Responsible Party

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

2-METHOXYETHYL ACETATE (EGMEA)

CAS: 110-49-6

RTECS: KL5950000

Fraction By Weight: 97.5%

OSHA PELS, 25 PPM

ACGIH TLV: S, 5 PPM; 9192

NON-AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED (O-5%)

Fraction By Weight: 2.5%

Hazards

Effects of Overexposure:EYES:LIQ CONTCT MAY IRRITATE;

SKIN:PROLNGD/REPEATED CONTCTMAY CAUSE IRRIT. MAYBE *SEE SUPPL
DATA*

First Aid

First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED ATTN;EYES:FLUSH IMMED W/WATER FOR AT LEAST 15 MIN. GET MED HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER FOR 15 MIN. FOR BURNS GET MED ATTN.

Fire Fighting

Flash Point:120F(49C)-TCC
Lower Limits:1.7
Upper Limits:8.2
Extinguishing Media:CO*2,DRY CHEM,DRY FOAM
Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPSD CONT W/WATER SPRAY.
Unusual Fire/Explosion Hazard:RUNOFF/SPILL MAY CAUSE POLLUTION/FIRE HAZARD

Accidental Release

Spill Release Procedures:ELIM IGN SOURCES.EVACUATE UNPROTECTED PERSONS.MFR STATE:HAVE GOOD VENTILATION-USE RESPIRATOR.CLEAN W/ABSORPTIVE-SAWDUST,RAGS,ETC.FLUSH WELL W/H*20.STATE/LOCAL LAWS TAKE PRECEDENCE;LG SPILL:DIKE LIQ & PUMP TO SALVAGE TANK PENDING DISPOSAL.

Handling

Handling and Storage Precautions:STORE AWAY FROM STRONG ALKALI.STORE IN COOL,DRY PLACE.KEEP CONTNRS TIGHTLY CLOSED. PROTECT CONTNRS FROM PHYSICAL DAMAGE.

Exposure Controls

Respiratory Protection:AN APPROVED ORGANIC VAP RESPIRATOR FOR EMERGENCY USE ONLY.
Ventilation:LOCAL EXHAUST & MECHANICAL(GENERAL) RECOMMENDED BY MFR.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES/GOGGLES
Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT.
Supplemental Safety and Health
MSDS FM MFR DTD:11-14-77.OVEREXPOSURE EFFECTS:ABSORBED THRU THE INTACT SKIN;INH:REPEATED/PROLONGED EXPOSURE TO HIGH CONC MAY RESULT IN CHANGES IN THE BLOOD PICTURE & POSSIBLE KIDNEY DAMAGE.

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:282-291F
Vapor Pres:3.3
Vapor Density:4.1
Spec Gravity:1.005
Solubility in Water:COMPLETE
Appearance and Odor:COLORLESS LIQUID-AROMATIC
Percent Volatiles by Volume:98%

Stability

Stability Indicator/Materials to Avoid:YES
NONE PER MFR.
Stability Condition to Avoid:SOURCE OF IGNITION
Hazardous Decomposition Products:BURNING MAY RESULT IN THE EVOLUTION OF CO & CO*2.

Disposal

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.COMPLY W/ALL APPLICABLE FED,STATE/LOCAL REGS REGARDING DISPOSAL;MFR SUGGESTS CONTROLLED BURNING METHOD OF DISPOSAL IAW FEDERAL,STATE & LOCAL EFFLUENT LAWS CONCERNING DISPOSAL PROCEDURES/METHODS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.