

167 8275,33 STOP BATH

MSDS Number

BCCFJ

National Stock Number

6750-00K001088

Product Name

167 8275,33 STOP BATH

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID:167 8275,33 STOP BATH

MSDS Date: 01/01/1985

FSC:6750

NIIN:00K001088 MSDS Number: BCCFJ

Responsible Party

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER, NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

AQUEOUS SOLUTION, HAZARD UNKNOWN, UNIDENTIFIED (90-95%)

Fraction By Weight: 92.5%

ACETIC ACID (SARA III)

CAS: 64-19-7

RTECS: AF1225000

Fraction By Weight: 7.5%

OSHA PEL10 PPM

ACGIH TLV: 10 PPM/15 STEL; 9192 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure: SKIN: PROLONGED/REPEATED CONTACT MAY CAUSE



IRRITATION & MAY RESULT IN ALLERGIC SKIN REACTION.

First Aid

First Aid:SKIN/EYES:FLUSH W/PLENTY OF WATER.GET MED ATTN FOR EYES;INH:REMOVE FROM EXPOSURE AREA.

Fire Fighting

Flash Point:NONE Lower Limits:NONE Upper Limits:NONE

Extinguishing Media:CO*2,DRY CHEM Unusual Fire/Explosion Hazard:NONE KNOWN

Accidental Release

Spill Release Procedures: ELIM IGN SOURCES.USE PROTECTV EQUIP, PROVIDE VENT.STOP LEAK W/O RISK.DIKE LG SPILL & PUMP INTO COVRD DRUMS; ABSORB/CONTAIN SMALL SPILL IN CONTNR PENDING DISPOSL; MFR RECOMMENDS, NEUTRLZ W/SOD BICARBONATE THEN FLUSH TO SEWER W/LG AMT H*20 IAW EXISTG REGS.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE

Other Precautions:AVOID PROLONGED/REPEATED CONTACT W/PRODUCT.REMOVE & WASH CONTAMINATED CLOTHING.WASH HANDS AFTER USE.APPROX PH OF PRODUCT:2.0

Exposure Controls

Respiratory Protection: NONE REQD IN NORMAL CONDITIONS.

Ventilation: MECHANICAL (GEN) IF NEEDED

Protective Gloves: IMPERVIOUS Eye Protection: SAFETY GLASSES

Other Protective Equipment: AS NEEDED BY LOCAL AUTHORITIES.

Supplemental Safety and Health

MSDS FM MFR DATED:10/11/76;ADDENDUM SHEET DT:2/19/81;SINGLE UNIT FOR

MIXING 15 GAL.

Chemical Properties

HCC:C1

Boiling Pt:B.P. Text:>212F/>100C

Vapor Pres:32 Vapor Density:0.7 Spec Gravity:1.010

Solubility in Water: COMPLETE

Appearance and Odor: COLORLESS LIQUID, ACETIC ACID ODOR

Percent Volatiles by Volume: 100

Stability

Stability Indicator/Materials to Avoid:YES
NONE PER MFR MSDS;HOWEVER AVOID FLAMM/OXIDIZING MATL.
Stability Condition to Avoid:UNK
Hazardous Decomposition Products:NONE PER MSDS

Disposal

Waste Disposal Methods: KEEP IN COVERED CONTAINERS PENDING DISPOSAL.DISPOSE IN FULL COMPLIANCE W/FEDERAL, STATE & LOCAL REGULATIONS; MFR RECOMMENDS TO FLUSH DOWN TO SEWER W COPIOUS AMT H*20.STATE & LOCAL EFFLUENT LAWS TAKE PRE CEDENCE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their



particular situation.