

PYRIDINE (SPECTRO GRADE) 13098

MSDS Number

BCCFV

National Stock Number

6810-00K001096

Product Name

PYRIDINE (SPECTRO GRADE) 13098

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID: PYRIDINE (SPECTRO GRADE) 13098 MSDS Date:01/01/1985 FSC:6810 NIIN:00K001096 MSDS Number: BCCFV

Responsible Party

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER, NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

PYRIDINE (SARA III)

CAS: 110-86-1

RTECS: UR8400000

Fraction By Weight: 100%

OSHA PEL5 PPM

ACGIH TLV: 5 PPM; 9192

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure: INH: HI VAP CONC CAUSES ANESTHESIA, RESP TRACT IRRIT.REPEATD VAP EXPSR MAY CAUS HEADACH*SEE SUPP DATA*

First Aid

First Aid:INH:REMOVE TO FRESH AIR.GIVE OXY/CPR IF NEEDED.CALL A PHYSICIAN; EYES: IMMED FLUSH W/PLENTY OF WATER FOR AT LEAST 15



MIN; SKIN: FLUSH W/PLENTY OF WATER.

Fire Fighting

Flash Point:47F(8C),TCC Lower Limits:1.8% Upper Limits:12.4

Extinguishing Media:CO*2,DRY CHEM,WATER.

Fire Fighting Procedures: AIR MASK SHOULD BE WORN.

Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures: ELIMINATE ALL SOURCES OF IGNITION. WEARING SUITABLE PROTECTIVE CLOTHING, ABSORB SPILLED MATL ON VERMICULITE. PLACE IN FIBER CARTON. WASH SPILLED AREA WELL W/WATER.

Handling

Handling and Storage Precautions: PLACE IN COOL DRY PLACE.PROTECT FROM PHYSICAL DAMAGE.KEEP CONTNRS TIGHTLY CLOSED.

Other Precautions: AVOID PROLONGED OR REPEATED CONTACT W/CHEMICAL.

Exposure Controls

Respiratory Protection: APPROVE SELF-CONTAINED BREATHING

APPARATUS/AIR-LINE RESPIRATOR.

Ventilation: LOCAL EXH/MECHANICAL(GEN).

Protective Gloves: RESISTANT

Eye Protection: SAFETY/CHEMICAL GOGGLES.

Other Protective Equipment: AS NECESSARY TO PREVENT SKIN CONTACT

Supplemental Safety and Health

NAUSEA, DIZZ, LOW BACK PAIN, URINARY FREQUENCY, KIDNEY/LIVER

EFFECTS; EYES: IRRIT & POSSIBLE CORNEAL

INJURY; SKIN: PROLONGED/REPEATED CONTACT CAN CAUSE SKIN IRRIT. MFGR

MSDS DATE 10/12/78.

Chemical Properties

HCC:F3

Boiling Pt:B.P. Text:244F,112C

Vapor Pres:16 Vapor Density:2.7 Spec Gravity:0.98

Solubility in Water: COMPLETE

Appearance and Odor: COLORLESS LIQD; CHARACTERISTIC DISAGREEABLE ODOR

Percent Volatiles by Volume: 100

Stability

Stability Indicator/Materials to Avoid:YES OXIDIZING MATL

Stability Condition to Avoid: SOURCE OF IGN.

Hazardous Decomposition Products:THERMAL DECOMP MAY PRODUCE NITROGE OXIDE GASES & CYANIDES.

Disposal

Waste Disposal Methods: WEARING SUITABLE PROTECTIVE EQUIPMENTS, INCINERATE IAW FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.