

186 0777, EKTAPRINT 2 DEVEL REPLNSHR, PART C

MSDS Number

BCCGN

National Stock Number

6750-00K001110

Product Name

186 0777, EKTAPRINT 2 DEVEL REPLNSHR, PART C

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID:186 0777, EKTAPRINT 2 DEVEL REPLNSHR, PART C

MSDS Date: 01/01/1979

FSC:6750

NIIN:00K001110

MSDS Number: BCCGN

Responsible Party

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER, NY 14650

Emergency Phone: 716-722-5151

Info Phone: LOCAL MARKETING & DISTRIBUTION CTR.

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

AQUEOUS SOLUTION, HAZARD UNKNOWN, UNIDENTIFIED COMPONENTS; WT%

CAS: 25646-77-9 RTECS: KJ6477000

Fraction By Weight: 77.5%

Hazards

Effects of Overexposure: EYES, SKIN, INHALE: IRRITNT; REPEATED SKIN CONTACT MAY CAUSE ALLERGIC SKIN REACTION; INGEST: HARMFUL.

First Aid

First Aid:INHALE:REMOVE TO FRESH AIR,GIVE CPR/O*2 IF NEED;EYES:FLUSH W LG AMTS H*20 FOR 15 MIN;SKIN:FLUSH W LG AMTS H*20;INGEST:RINSE MOUTH;GET IMMEDIATE MEDICAL ATTENTION FOR EYES OR INGEST.NOTE:IRRITATION MAY BE DUE TO SO*2 GAS/VAPOR.

Fire Fighting

Extinguishing Media:SUITABLE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP;H*20 SPRAY COOL CONT.



Unusual Fire/Explosion Hazard: CONTAINERS MAY RUPTURE IN HEAT OF FIRE.

Accidental Release

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS.STOP LEAK. H*20 SPRAY HOT CONTAINERS.ABSORB WITH COMMERCIAL ABSORBENT, SHOVEL INTO WASTE DISPOSAL CONTAINERS; LG SPILL: DIKE WITH COMMERCIAL ABSORBENT, TRANSFER INTO WASTE DIS POSAL CONTAINERS.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA;PROTECT FROM PHYSICAL DAMAGE & AVOID CONTACT.KEEP CONTAINERS TIGHTLY CLOSED.DO NOT STORE NEAR STRONG CAUSTIC Other Precautions:REMOVE & WASH CONTAMINATED CLOTHING.MAINTAIN STRICT HYGIENE.USE OF NON-ALKALINE(ACID) TYPE HAND CLEANER REDUCES RISK OF ALLERGIC SKIN REACTION.SO*2 IS LIBERATED FROM CONCENTRATE:TLV=2 PPM

Exposure Controls

Ventilation: ADEQUATE TO ELIMINATE MISTS: MECHANICAL (GENERAL)/LOCAL EXH. Protective Gloves: IMPERVIOUS Eye Protection: SAFETY/CHEM GOGGLES.
Other Protective Equipment: FULL WORK CLOTHING; FACE SHIELD WHEN USING/MIXING PRODUCT.
Supplemental Safety and Health

Respiratory Protection: WEAR APPR RESPIRATOR FOR SO*2 GAS, IF NEEDED

MSDS FROM MFG DATED 5/1/78, REISSUED 5/78. PH IS APPROX 1.0; PART C OF THREE PART PRODUCT. STORAGE CODE BASED UPON DISSOCIATION PRODUCT, SULFURIC ACID, *MONOHYDRATE(20-25%). SEE ADD DATA.

Chemical Properties

HCC:C1

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:17 Vapor Density:0.6 Spec Gravity:1.16

Solubility in Water: COMPLETE

Appearance and Odor: CLEAR, AMBER AQUEOUS SOLUTION; SHARP ODOR OF SO*2.

Percent Volatiles by Volume:62

Stability

Stability Indicator/Materials to Avoid:YES MINERAL ACIDS & STRONG ALKALI. Stability Condition to Avoid:VAPOR GENERATING CONDITIONS. Hazardous Decomposition Products:SO*2;EXPECT CO,CO*2 FROM ORGANIC COMBUST.

Disposal

Waste Disposal Methods: KEEP IN COVERED CONTAINERS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE & LOCAL REGULATIONS. MFG SUGGESTS FLUSH TO SEWER WITH EXCESS WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.