126 0793,EKTAPRINT 2 DEVEL REPLNSHR, PART D

MSDS Number

BCCGY

National Stock Number

6750-00K001117

Product Name

126 0793, EKTAPRINT 2 DEVEL REPLNSHR, PART D

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID:126 0793, EKTAPRINT 2 DEVEL REPLNSHR, PART D

MSDS Date:01/06/1978

FSC:6750

NIIN:00K001117 MSDS Number: BCCGY

Responsible Party

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER, NY 14650

Emergency Phone: 716-722-5151

Info Phone: LOCAL MARKETING & DISTRIBUTION CTR.

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

_..__

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

POTASSIUM CARBONATE; CAS# 584-08-7; WT% RANGE 35-40%

CAS: 584-08-7 RTECS: TS7750000

Fraction By Weight: 37.5%

POTASSIUM HYDROXIDE (SARA III)

CAS: 1310-58-3 RTECS: TT2100000 Fraction By Weight: OSHA PELC, 2 MG/M3

ACGIH TLV: C 2 MG/M3; 9192 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS



AQUEOUS SOLUTION, HAZARD UNKNOWN, UNIDENTIFIED INGREDIENTS;

Fraction By Weight:

Hazards

Effects of Overexposure:EYES:BURNS;SKIN:PROLONGED OR REPEAT CONTACT:IRRITNT:INGEST:PAIN,VOMIT;INHALE:SHORT BREATH

First Aid

First Aid: EYES, SKIN, MUCOUS MEMBRANES: FLUSH W LG AMTS H*20 AT LEAST 15 MIN; INHALE: REMOVE TO FRESH AIR, KEEP CALM; INGEST: RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, INGEST, OR BURNS-ADVISE PHYSICIAN THAT PRODUCT IS CAUSTIC SOLUTION, TREAT ACCORDINGLY.

Fire Fighting

Extinguishing Media:NOT COMBUSTIBLE:USE MEDIA SUITABLE FOR ADJACENT FIRE.

Fire Fighting Procedures: WEAR SELF-CNTND BRTHG APP; H*20 SPRAY COOL CONT.

Unusual Fire/Explosion Hazard: CONTAINERS MAY RUPTURE IN HEAT OF FIRE.

Accidental Release

Spill Release Procedures: DO NOT TOUGH SPILLED MATERIAL. WEAR PROTECTIVE EQUIPMENT. STOP LEAK IF POSSIBLE WITHOUT RISK. SM SP: ABSORB W COMMERCIAL ABSORBENT & PUT IN APPR CONTAINERS. LG SP: CONTAIN W DIKE & TRANSFER TO APPR CONTAINERS.

Handling

Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED, LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE. AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions: AVOID PROLONGED OR REPEATED CONTACT W CHEMICAL.REMOVE & WASH CONTAMINATED CLOTHING. DISCARD CONTAMINATED SHOES. MAINTAIN STRICT HYGIENE. STORE AWAY FROM STRONG MINERAL ACIDS.

Exposure Controls

Respiratory Protection: NO SPECIAL REQUIREMENTS

Ventilation: MECHANICAL (GEN./LOCAL EXHAUST) AS NECESSARY TO CONTROL MIST

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY/CHEM GOGGLES.

Other Protective Equipment: NORMAL FULL WORK CLOTHING COVERING

ARMS, LEGS.

Supplemental Safety and Health

MSDS FROM MFG DATED 5/1/78, REISSUED 5/78. PART D OF FOUR PART

PRODUCT.PH IS APPROX 14 (CAUSTIC).

Chemical Properties

HCC:C2

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:17 Vapor Density:0.6 Spec Gravity:1.45

Solubility in Water: COMPLETE

Appearance and Odor: CLEAR, COLORLESS AQUEOUS SOLUTION; ODORLESS

Percent Volatiles by Volume:60

Stability

Stability Indicator/Materials to Avoid:YES AVOID STRONG MINERAL ACIDS Stability Condition to Avoid:MIST GENERATING CONDITIONS Hazardous Decomposition Products:EXPECT CO*2,PER MFG.

Disposal

Waste Disposal Methods: DISPOSE IN FULL ACCORD WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS. MFG SUGGESTS NEUTRALIZE WITH SODIUM BICARBONATE & FLUSH TO SEWER WITH EXCESS



WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.