

190 1545, FLEXCOLR HV BLEACH REGNRATR, PART B

MSDS Number

BCCHZ

National Stock Number

6750-00K001139

Product Name

190 1545, FLEXCOLR HV BLEACH REGNRATR, PART B

Manufacturer

FASTMAN KODAK COMPANY

Product Identification

Product ID:190 1545, FLEXCOLR HV BLEACH REGNRATR, PART B

MSDS Date: 01/01/1985

FSC:6750

NIIN:00K001139 MSDS Number: BCCHZ

Responsible Party

EASTMAN KODAK COMPANY

Emergency Phone: 716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

AMMONIUM(ETHYLENEDINITRILO)TETRAACETO)-FERRATE(III)(40-45%)

Fraction By Weight: 45.0%

AMMONIUM HYDROXIDE (SARA III)

CAS: 1336-21-6

RTECS: BQ9625000

Fraction By Weight: 10.0% EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

WATER(40-45%) (CAS #7732-18-5)

CAS: 7732-18-5 RTECS: ZC0110000

Fraction By Weight: 45.0%

Hazards

Effects of Overexposure: MSDS FM MFR STATES THAT EFFECTS OF OVEREXPOSURE ARE OF LOW HAZ ARD TO HEALTH.



First Aid

First Aid: PER MFR MSDS IN CASE OF CONTACT W/LIQD, FLUSH AREA W/PLENTY OF WATER.GET MED ATTN IF NEEDED OR SYMPTOMS OCCUR.

Fire Fighting

Flash Point:NONE Lower Limits:NONE Upper Limits:NONE

Extinguishing Media:CO*2,FOAM,DRY CHEM Unusual Fire/Explosion Hazard:NONE KNOWN

Accidental Release

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS, PROVIDE VENTILATION/SAFETY EQUIPMENTS IF NECESSARY. DIKE LG SPILL & PUMP INTO COVERED CONTNRS; ABSORB SM SPILL W/ABSORBING MATL & PLACE IN SAME CONTNR; MFR SUGGESTS FLUSH DOW N TO SEWER W/LG AMT OF H*20 IAW EXISTING REGS.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA.KEEP CONTNRS TIGHTLY CLOSD.PROTECT CONTNRS FROM PHYSICAL DAMAGE.

Other Precautions: AVOID PROLONGED/REPEATED CONTACT W/PRODUCT.REMOVE & WASH CONTAMINATED CLOTHING. WASH HANDS AFTER USE. APPROX PH OF PRODUCT: 7.0

Exposure Controls

Respiratory Protection: NONE REQD IN NORMAL CONDITIONS.

Ventilation: MECHANICAL (GEN) IF NEEDED

Protective Gloves: IMPERVIOUS Eye Protection: SAFETY GLASSES

Other Protective Equipment: AS NEEDED BY LOCAL AUTHORITIES.

Supplemental Safety and Health

MSDS FM MFR DATED:6/3/82 & FORMULA DATE 1/6/82;ITEM IS A 2 PART PRODUCT.THIS DATA IS FOR "HV BLEACH REGENERATOR,PART B";UNIT CONTNR

QTY YIELDS-100 GAL.

Chemical Properties

HCC:B3

Boiling Pt:B.P. Text:>212F/>100C

Vapor Pres:17 Vapor Density:0.6 Spec Gravity:1.29

Solubility in Water: COMPLETE

Appearance and Odor:OPAQUE,,REDDISH-BROWN SOLN;SLIGHT AMMONICAL ODOR

Percent Volatiles by Volume: 55%

Stability

Stability Indicator/Materials to Avoid:YES NONE

Disposal

Waste Disposal Methods: KEEP IN COVERED CONTAINERS PENDING DISPOSAL.DISPOSE IN FULL COMPLIANCE W/FEDERAL, STATE & LOCAL REGULATIONS; MFR RECOMMENDS TO FLUSH DOWN TO SEWER W COPIOUS AMT H*20.STATE & LOCAL EFFLUENT LAWS TAKE PRE CEDENCE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

