

35-BK-1 CATALYST, BLACK 17038, ISOCYANATE

MSDS Number

BCCJH

National Stock Number

8010-00K001202

Product Name

35-BK-1 CATALYST, BLACK 17038, ISOCYANATE

Manufacturer

DEFT CHEMICAL COATINGS

Product Identification

Product ID:35-BK-1 CATALYST,BLACK 17038,ISOCYANATE

MSDS Date:01/01/1985

FSC:8010

NIIN:00K001202 MSDS Number: BCCJH

Responsible Party

DEFT CHEMICAL COATINGS

17451 VON KARMAN AVE

IRVINE, CA 92714-6205

US

Cage: EO418

Contractor

DEFT, INC.

IRVINE, CA 92614

US

949-474-0400 Cage: 33461

Ingredients

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7 RTECS: ZE2100000

Fraction By Weight: 12.5%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 12.5%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192



BIURET OF 1,6 HEXAMETHYLENE DIISOCYANATE (APPROX

Fraction By Weight: 74.5%

1,6-DIISOCYANATOHEXANE (HEXAMETHYLENE DIISOCYANATE)

CAS: 822-06-0 RTECS: MO1740000

Fraction By Weight: 0.5% ACGIH TLV: 0.005 PPM; 9192

EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

Hazards

Effects of Overexposure: EYES: MODERATE IRRIT; SKIN: POSSIBLE IRRIT BY SOLVENTS; INH: SOLVENT VAPORS CAN CAUSE IRRIT OR NARCOSIS.

First Aid

First Aid:SKIN:WIPE OFF WITH A RAG THEN THOROUGH RINSING W/H*20 & WASHING W/MILD SOAP AND WATER;EYES:FLUSH W/WATER FOR AT LEAST 10 MIN & CONSULT AN EYE PHYSICIAN;INH:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDE D.

Fire Fighting

Flash Point:101F(38C)-TCC

Extinguishing Media: CARBON DIOXIDE, FOAM OR DRY CHEMCIALS Fire Fighting Procedures: USE SELF-CNTND BRTHNG APP; CAN USE H^*2O

SPRAY/FOG EFFECTIVLY.

Unusual Fire/Explosion Hazard: NONE KNOWN

Accidental Release

Spill Release Procedures: EVACUATE UNPROTCTD PERSONS.ELIM IGN SURCES.USE SAFETY EQUIP. VENTILATE AREA. STOP LEAK W/O RISK; ABSORB SM SPILL W/OIL ABSORBING COMPD/RAGS. PER MFR, FLUSH ARA W/LG AMT H*20; DIKE LG SPILL. PUMP LIQ TO SALVA GE TANK. SHOVEL UP RESIDUE INTO COVERED CONTNRS.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW FIRE RISK AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTCT FROM PHYSICAL DAMAGE.

Other Precautions: AVOID PROLONGED INHALATION OF VAPORS. IF VENTILATION IS POOR, A FRESH AIR SUPPLY MASK IS RECOMMENDED. AVOID PHYSICAL CONTACT.

Exposure Controls

Respiratory Protection: NIOSH APPROVED RESPIRATOR FOR

PAINT,LAQUER,ENAMEL MIST& ORGANIC VAP Ventilation:ADEQUATE USING EXHAUST FAN. Protective Gloves:NEOPRENE/RUBBER

Eye Protection: SAFETY/CHEM GOGGLE W/SHLD

Other Protective Equipment: USE CARTRIDGE TYPE RESPIRATOR W/PARTICULATE FILTERS.

Supplemental Safety and Health

TWO PART RESIN MODIFIED POLYURETHANE COATING: THIS DATA FOR CATALYST: MFR ALSO IDENTIFIED AS "DEFTHANE CATALYST". KEY1: F4.

Chemical Properties

Boiling Pt:B.P. Text:325F/162.8C

Spec Gravity:1.06



Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR,PALE YELLOW LIQ;XYLENE/GLYCOL ACETATE ODOR Percent Volatiles by Volume:25%

Stability

Stability Indicator/Materials to Avoid:YES WATER,ALCOHOLS,AMINES & OTHER COMPDS WHICH REACT W/ISOCYNATE Stability Condition to Avoid:SOURCES OF IGNITION Hazardous Decomposition Products:CO,CO*2 &/OR OXIDES OF NITROGEN

Disposal

Waste Disposal Methods: KEEP IN CLOSED CONTNRS PENDING DISPOSAL.MFR SUGGESTED, DISPOSE IN TIGHTLY CLOSED CONTAINERS & FINALLY DISPOSE BY SANITARY LANDFILL.INCINERATE WASTE UNDER CONDITIONS WHICH MEET FED, STATE & LOCAL ENVIRON MENTAL CONTROL REGULATIONS (NEVER INCINRATE CONTNR)

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.