

03-BL-59 CATALYST,BLUE 35109,ISOCYANATE

MSDS Number

BCCJR

National Stock Number

8010-00K001207

Product Name

03-BL-59 CATALYST,BLUE 35109,ISOCYANATE

Manufacturer

DEFT CHEMICAL COATING

Product Identification

Product ID:03-BL-59 CATALYST,BLUE 35109,ISOCYANATE

MSDS Date:01/01/1985

FSC:8010

NIIN:00K001207

Kit Part:Y

MSDS Number: BCCJR

Responsible Party

DEFT CHEMICAL COATING

17451 VON KARMAN AVE

IRVINE , CA 92714-6205

US

Cage: EO418

Contractor

DEFT, INC.

IRVINE, CA 92614

US

949-474-0400

Cage: 33461

Ingredients

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 22.8%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:EYE IRRITNT,SOLVENTS MAY IRRITAT SKIN.MAY IRRITAT OR CAUSE NARCOSIS IF INHALED

First Aid

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES:FLUSH W LG AMTS H*20 FOR 15 MIN;SKIN:FLUSH W LG AMTS H*20;INGEST:RINSE MOUTH.

Fire Fighting

Flash Point:28F/-2.2C TOC
Lower Limits:1.44
Upper Limits:UNK
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:WEAR SCUBA,WATER SPRAY TO COOL EXPOS
CONT;DONOT USE H*2O JE
Unusual Fire/Explosion Hazard:CONTR MAY EXPLODE IN HEAT OF FIRE. DO NOT
APPLY TO HOT SURFACES.AVOID SPARKS,OPEN FLAMES.

Accidental Release

Spill Release Procedures:DO NOT TOUCH SPILLED MATL. ELIMINATE IGNITION
SOURCES. EXCLUDE UNPROTECTED PERSONS FROM AREA. SM SPILL: ABSORB W.
SAND,EARTH,OTHER ABSORB MATL.,THEN FLUSH W. H*2O. LG SPILL: STOP
LEAK, DIKE FOR LATER DISPOSAL.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW
FIRE RISK AREA.KEEP CONTAINERS CLOSED(MOISTURE SENSITIVE).PROTECT
FROM PHYSICAL DAMAGE.
Other Precautions:MAINTAIN STRICT HYGIENE,AVOID PHYSICAL CONTACT,REMOVE
&WASH CONTAMINATED CLOTHING.AVOID PROLONGED INHALATION OF VAPORS.
USE FRESH AIR SUPPLY MASK IF VENTILATION IS POOR.

Exposure Controls

Respiratory Protection:SCBA, SUPPLIED AIR RESPIRATOR
Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE
VENTILATION
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment:CARTRIDGE TYPE RESPIRATOR WITH PARTICULATE
FILTERS.
Supplemental Safety and Health
2 PART RESIN MODIFIED POLYURETHANE COATING. SPEC. REF:NAI-1290. ITEM
ALSO KNOWN AS DEFTHANE ENAMEL CATALYST. KEY1: J1.

Chemical Properties

Boiling Pt:B.P. Text:160-3139
Vapor Pres:UNK
Vapor Density:>1
Spec Gravity:0.95
Evaporation Rate & Reference:Appearance and Odor:CLEAR,WATER WHITE LIQ;METHYL ETHYL KETONE ODOR.
Percent Volatiles by Volume:75.5

Stability

Stability Indicator/Materials to Avoid:YES
AVOID WATER,ALCOHOLS,CMPD WHICH REACT W. ISOCYANATES.
Stability Condition to Avoid:AVOID IGNITION SOURCES
Hazardous Decomposition Products:IF COMBUSTED: CO*2, CO, TOXIC
HYDROCARBS, OTHER TOXIC OXIDES

Disposal

Waste Disposal Methods:SM & LG SPILL:DEPOSIT IN A POSTED TOXIC
SUBSTANCE LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL
REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.