

# **EPIBOND 8262-B**

#### **MSDS Number**

**BCCTC** 

#### **National Stock Number**

8030-00K001347

#### **Product Name**

EPIBOND 8262-B

#### Manufacturer

FURANE PRODUCTS M AND T CHEMICALS INC

# **Product Identification**

Product ID: EPIBOND 8262-B MSDS Date: 01/01/1987 FSC:8030 NIIN:00K001347 MSDS Number: BCCTC

# **Responsible Party**

FURANE PRODUCTS; M & T CHEMICALS, INC.

Emergency Phone: 213-247-6210

Cage: GO766

### Contractor

CIBA SPECIALTY CHEMICALS CORP, N. A. / PERFORMANCE

LOS ANGELES, CA 90039-1011

US

818-247-6210/800-873-1138

Cage: GO766

### **Ingredients**

POLY AMINO AMIDE

Fraction By Weight: 100%

#### Hazards

Effects of Overexposure: EXPECT CONTACT DERMATITIS IN ALLERGIC

**INDIVIDUALS** 

# First Aid

First Aid: INHALE: REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF NEED; EYES/SKIN: FLUSH W/LG AMTS H\*20 FOR 15 MIN; INGEST: RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFUCULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

# **Fire Fighting**

Flash Point:>300F,>148C(COC)

Extinguishing Media: WATER, OR ANY COMMERCIAL UNIT.

Fire Fighting Procedures: NIOSH/MSHA APPROV SCBA.H\*20 SPRAY COOL

CONT, KNOCK DOWN VAP.

Unusual Fire/Explosion Hazard: MATL MAY/MAY NOT BURN. CONTAINER MAY EXPLODE IN HEAT OF FIRE.FIRE MAY YIELD TOXIC GASES.

#### **Accidental Release**

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. STOP LEAK. H\*20 SPRAY COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W/COMMERCIAL



ABSORBENT, SHOVEL INTO METAL DRUMS: LG SPILL: DI KE W COMMERCIAL ABSORBENT, PUMP INTO COVERED DRUMS.

### Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions: MAINTAIN STRICT HYGIENE, AVOID PHYSICAL CONTACT, REMOVE & WASH CONTAMINATED CLOTHING. MFG SUGGESTS USE OF PROTECTIVE SKIN CREAMS. EXHAUST CURING OVENS TO OPEN AIR. AVOID TEMPERATURE EXTREMES.

# **Exposure Controls**

Respiratory Protection: NO SPECIAL REQMNTS UNDER ORDINARY

CONDITIONS/ADEQUATE VENT.

Ventilation: MECHANICAL (GENERAL/LOCAL EXHAUST)

Protective Gloves: PV/RUBBER

Eye Protection: SAFETY/CHEM GOGGLES

Other Protective Equipment: FULL WORK CLOTHING TO PREVENT REPEATED OR

PROLONGED CONTACT.

Supplemental Safety and Health

PART B OF 2 PART PRODUCT. THIS PART IS HARDNER. SEE P/N A FOR PART A

(RESIN).KEY1:N1.

# **Chemical Properties**

HCC:N1

Boiling Pt:B.P. Text:DECOMPOSES

Spec Gravity: 1.05

Solubility in Water: NEGLIGIBLE

Appearance and Odor: AMBER LIQUID; STRONG AMINE ODOR.

Percent Volatiles by Volume:0

# **Stability**

Stability Indicator/Materials to Avoid:YES

ACIDS, PEROXIDES

Stability Condition to Avoid: HEAT OR STORAGE AT TEMPERATURES ABOVE

90F; IGNITION SOURCES.

Hazardous Decomposition Products:NONE NOTED, BUT EXPECT CO, CO\*2,H\*2O &

AMINE FRAGMENTS.

# **Disposal**

Waste Disposal Methods: KEEP IN COVERED CONTAINERS PENDING DISPOSAL.HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE & LOCAL REGULATIONS. MFG SUGGESTS INCINERATION OR BURY IN APPROVED LANDFI LL, WASH RESIDUE W/DETERGENT, EXCESS H\*20.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.