

## **1063-P-166,PAINT PRIMER**

### **MSDS Number**

BCCTN

### **National Stock Number**

8010-00K001401

### **Product Name**

1063-P-166,PAINT PRIMER

### **Manufacturer**

E I DUPONT DE NEMOURS AND CO INC

### **Product Identification**

Product ID:1063-P-166,PAINT PRIMER

MSDS Date:01/01/1985

FSC:8010

NIIN:00K001401

MSDS Number: BCCTN

### **Responsible Party**

E.I.DUPONT DE NEMOURS & CO,INC

1007 MARKET STREET

WILMINGTON , DE 19899

US

Emergency Phone: 800-441-7515

Info Phone: 800-441-7515

Cage: DO229

### **Contractor**

E.I.DUPONT DE NEMOURS & CO INC

1635

BOSTON, MA 02118

US

800-441-7515

Cage: DO229

### **Ingredients**

PHENOLIC RESIN

Fraction By Weight: 8%

ACGIH TLV: 5 PPM

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 2 - 8%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

#### ALIPHATIC ALCOHOL

Fraction By Weight: 8%

ACGIH TLV: 400 PPM

#### ALIPHATIC PETROLEUM DISTILLATE

Fraction By Weight: 23%

ACGIH TLV: 500 PPM

#### ZINC (SARA III)

CAS: 7440-66-6

RTECS: ZG8600000

Fraction By Weight: 8%

OSHA PEL10 MG ZNO/M3

ACGIH TLV: 10 MG ZNO/M3; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

### Hazards

Effects of Overexposure: HEADACHE, NAUSEA, IMPAIRMENT OF REACTION TIME AND COORDINATION.

### First Aid

First Aid: REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. SKIN: WASH WITH SOAP & WATER. EYES: FLUSH WITH WATER 15 MIN. KEEP WARM AND QUIET !

### Fire Fighting

Flash Point: 20-80°F TOC

Lower Limits: 1.0

Upper Limits: 12.0

Extinguishing Media: CO<sub>2</sub>, FOAM, DRY CHEM.

Fire Fighting Procedures: USE H<sub>2</sub>O TO COOL EXPD CONTRS. USE SCBA & FULL PROT. CLTHG.

Unusual Fire/Explosion Hazard: NONE NOTED BY MANUFACTURER.

### Accidental Release

Spill Release Procedures: REMOVE IGNITION SOURCES, VENTILATE AREA WELL. ABSORB WITH VERMICULITE OR OTHER MATERIALS, SUCH AS SAWDUST, RAGS, PAPER & PLACE IN CLOSED CONTAINER. USE NON SPARKING TOOLS. WEAR PROPER PROTECTIVE EQUIPMENT DURING CLEAN UP.

### Handling

Handling and Storage Precautions: KEEP AWAY FROM IGNITION SOURCES. KEEP CONTAINERS CLOSED.

Other Precautions: WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR SMOKING. OBSERVE LABEL PRECAUTIONS. CONTAINERS SHOULD BE GROUNDED WHEN POURING.

### Exposure Controls

Respiratory Protection: USE ADEQUATE VENTILATED AREAS, USE BUR MINE APPROVED MASKS.

Ventilation: LOCAL EXHAUST TO MAINTAIN BELOW TLV AND LEL.

Protective Gloves: IMPERVIOUS

Eye Protection: CHEM SPLASH GOGGLES

Other Protective Equipment: USE APPROPRIATE HYGIENE PRACTICES.

Supplemental Safety and Health  
NIOSH 6:GB4200000,CHROMIUM,CAS# 7440-47-3,7%,TLV-1 MG/CUM.NIOSH  
7:OF7525000,LEAD CAS# 7439-92-1,0.07%,TLV-0.15 MG/CUM.BP  
RANGE:80-175C.FL PT RANGE:-6.7-27C TOC.

## Chemical Properties

HCC:F3  
Boiling Pt:B.P. Text:176-347F  
Vapor Pres:37  
Vapor Density:3.14  
Spec Gravity:1.248  
Evaporation Rate & Reference:>1(ETHER=1)  
Solubility in Water:MODERATE  
Appearance and Odor:SEMI-VISCOUS YELLOW LIQUID,TYPICAL SOLVENT ODOR.  
Percent Volatiles by Volume:57.6

## Stability

Stability Indicator/Materials to Avoid:YES  
NONE REASONABLY FORESEEN.  
Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE,OXIDES  
OF ZINC,LEAD,CHROMIUM.

## Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &  
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE  
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.