

URETHANE ENAMEL,BLACK, 826Y AH699 (99-U)

MSDS Number

BCCVM

National Stock Number

8010-00K001421

Product Name

URETHANE ENAMEL,BLACK, 826Y AH699 (99-U)

Manufacturer

E I DUPONT DE NEMOURS AND COMPANY INC

Product Identification

Product ID:URETHANE ENAMEL,BLACK, 826Y AH699 (99-U)

MSDS Date:01/01/1985

FSC:8010

NIIN:00K001421

MSDS Number: BCCVM

Responsible Party

E.I.DUPONT DE NEMOURS & COMPANY,INC

1007 MARKET STREET

WILMINGTON , DE 19899

US

Emergency Phone: 800-441-7515

Info Phone: 800-441-7515

Cage: DO229

Contractor

E.I.DUPONT DE NEMOURS & CO INC

1635

BOSTON, MA 02118

US

800-441-7515

Cage: DO229

Ingredients

ETHER ESTER

Fraction By Weight: 33.0%

ACGIH TLV: 100PPM(PER MFR)

ALIPHATIC ESTER

Fraction By Weight: 27.0%

ACGIH TLV: 400PPM(PER MFR)

ALIPHATIC PETROLEUM DISTILLATE

Fraction By Weight: 3.0%

ACGIH TLV: 100PPM(PER MFR)

NON AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED; WT % BY

Fraction By Weight: 37.0%

Hazards

Effects of Overexposure:CAUSE COUGHING,CHEST PAINS & BREATHING
DIFFICULTY MAY OCCUR,EARLY SIGNS MAY BE MISTKN FOR A COLD.

First Aid

First Aid:INHALATION:MOVE TO FRESH AIR TO IMPROVE BREATHING;SKIN:WASH
WITH SOAP & WATER.REMOVE CONTAMINATED CLOTHING;EYES:FLUSH WITH
WATER FOR AT LEAST 15 MIN.CALL A PHYSICIAN.

Fire Fighting

Flash Point:20-73F (CC)

Lower Limits:1.0

Upper Limits:11.2

Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:COOL CLOSED CONTNRS W/H*20 USING FOG NOZZLES.

Unusual Fire/Explosion Hazard:WARNING: VAPOR & SPRAY MISTS ARE HARMFUL

Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION
SOURCES. STOP LEAK. H*20 SPRAY COOL CONT/DIVERT SPILL FROM
FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL
ABSORBENT,SHOVEL INTO METAL DRUMS:LG SPILL:DI KE W COMMERCIAL
ABSORBENT,PUMP INTO COVERED DRUMS.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS & OPEN
FLAMES.CLOSE CONTAINERS AFTER EACH USE.DO NOT STORE ABOVE 120F
Other Precautions:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR
SMOKING;OBSERVE LABEL PRECAUTIONS;CONTAINERS SHOULD BE GROUNDED
WHEN POURING;ALLRGY-PRONE PERSONS MAY BE SENSITZD,SHOULD NOT BE
EXPOSED.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA RESP TC-19C IF AIR CONTMNANTS
CONTROL IS NOT FEASIBLE

Ventilation:LOCAL & MECH PROVIDE SUFFICIENT VENT TO KEEP BELOW TLV
LEVEL

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:USE APPROPRIATE INDUSTRIAL HYGIENE
PRACTICES.

Supplemental Safety and Health

MSDS FM MFR DATED:03/28/80

Chemical Properties

HCC:F3

Boiling Pt:B.P. Text:168-347F

Vapor Pres:1.2

Vapor Density:4.7

Spec Gravity:1.006

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:MODERATE

Appearance and Odor:LIQUID PAINT WITH CHARACTERISTIC ODOR

Percent Volatiles by Volume:69.3

Stability

Stability Indicator/Materials to Avoid:YES

OXIDIZERS, CORROSIVES

Stability Condition to Avoid:HEAT, IGNITION SOURCES;DO NOT MIX ACTVTR
UNTIL READY TO USE.

Hazardous Decomposition Products:CO,CO*2,SMOKE,NITROGEN,OXIDES OF

NITROGEN

Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.