

CERTI-FIRE 9680 RESISTOR

MSDS Number

BCCWN

National Stock Number

5905-00K001443

Product Name

CERTI-FIRE 9680 RESISTOR

Manufacturer

E I DUPONT DE NEMOURIS AND CO INC

Product Identification

Product ID: CERTI-FIRE 9680 RESISTOR

MSDS Date: 01/01/1985

FSC: 5905

NIIN: 00K001443

MSDS Number: BCCWN

Responsible Party

E.I. DUPONT DE NEMOURIS & CO, INC.

Emergency Phone: 302-774-2421

Cage: 19898

Contractor

E.I. DUPONT DE NEMOURS & CO., INC.

1635

WILMINGTON, DE 19898

US

800-441-7515; 800-441-9442

Cage: 19898

Ingredients

GLASS, FIBROUS

RTECS: LK3651000

Fraction By Weight: 69%

OSHA PEL15 MG/M3 (DUST)

ACGIH TLV: 10 MG/M3 (DUST); 9192

CELLULOSE TYPE RESIN, (29-33%), SEE ADDITIONAL DATA FOR

Fraction By Weight: 30%

PHOSPHATIDYL CHOLINE, ((LECITHIN)), (0-2%)

Fraction By Weight: 1%

PINE OIL DERIVATIVE (PRINCIPAL SOLVENT)

Fraction By Weight: UNK

PHTHALATE ESTER,UP TO 50% OF SOLVENT SYSTEM.

Fraction By Weight: UNK

Hazards

Effects of Overexposure:ERYTHEMA,KIDNEY DAMAGE-BAY ANALOGY TO PINE OIL.

First Aid

First Aid:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. SKIN:WASH WITH SOAP & WATER. EYES:FLUSH WITH WATER 15 MIN. KEEP WARM AND QUIET !

Fire Fighting

Flash Point:190F/88C COC

Lower Limits:UNK

Upper Limits:UNK

Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP IF INVOLVED IN FIRE.

Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

Accidental Release

Spill Release Procedures:ELIMINATE IGNITION SOURCES.AVOID PROLONGED CONTACT WITH SKIN & PROLONGED BREATHING OF VAPOR.SM DRY SPILL:SWEEP UP & PLACE IN CLOSED CONTAINER.LIQ SPILL WIPE UP WITH RAGS.PLACE IN CLOSED CONTAINER UNTI L DISPOSED.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED. MAINTAIN STANDARD HYGIENE FOR CHEM HANDLING

Other Precautions:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR SMOKING.OBSERVE LABEL PRECAUTIONS.

Exposure Controls

Respiratory Protection:USE WITH ADEQUATE VENTILATION.

Ventilation:LOCAL EXHAUST THAT PROVIDES SUFFICIENT VENTILATION.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:USE APPROPRIATE HYGIENE PRACTICES.

Supplemental Safety and Health

NIOSH 1:GLASS POWDER IS COMBINATIN RETHENIUM PYCHLORE & GLASSES COMPOSD OF ONE OR MORE OF FOLLOWING ELEMENTS:BARIUM,BISMUTH,BORON,CADMIUM,LEAD,SILICON,TITANIUM.

Chemical Properties

HCC:V4

Boiling Pt:B.P. Text:428F/220C

Vapor Pres:Vapor Density:UNK

Spec Gravity:0.94

Evaporation Rate & Reference:Solubility in Water:NEGLIGIBLE

Appearance and Odor:NO INFORMATION AVAILABLE

Percent Volatiles by Volume:100

Stability

Stability Indicator/Materials to Avoid:YES

NONE NOTED BY MFR.

Hazardous Decomposition Products:NONE NOTED,BUT EXPECT CO, CO*2, H*2O.

Disposal

Waste Disposal Methods:ELIMINATE IGNITION SOURCES. DESTROY BY LIQUID INCINERATION. INCINERATION WILL BE EASIER BY MIXING WITH A MORE FLAMMABLE SOLVENT. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,F ED,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.