

## **DULUX ENAMEL, CLEAR, RK-190(190S),(3/1/74)**

### **MSDS Number**

BCCYN

### **National Stock Number**

8010-00K001480

### **Product Name**

DULUX ENAMEL, CLEAR, RK-190(190S),(3/1/74)

### **Manufacturer**

E I DUPONT DE NEMOURS AND COMPANY INC

### **Product Identification**

Product ID:DULUX ENAMEL, CLEAR, RK-190(190S),(3/1/74)

MSDS Date:01/01/1985

FSC:8010

NIIN:00K001480

MSDS Number: BCCYN

### **Responsible Party**

E.I.DUPONT DE NEMOURS & COMPANY,INC

1007 MARKET STREET

WILMINGTON , DE 19899

US

Emergency Phone: 800-441-7515

Info Phone: 800-441-7515

Cage: DO229

### **Contractor**

E.I.DUPONT DE NEMOURS & CO INC

1635

BOSTON, MA 02118

US

800-441-7515

Cage: DO229

### **Ingredients**

AROMATIC PETROLEUM DISTILLATE(BY ANALOGY TO XYLENE)

Fraction By Weight: 24.0%

ACGIH TLV: 100PPM(PER MFR)

NON-AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED(BALANCE BY

Fraction By Weight: 47.0%

ALIPHATIC PETROLEUM DISTILLATE(ANALOG TO HEPTANE & OCTANE)

Fraction By Weight: 29.0%

ACGIH TLV: 400PPM(PER MFR)

### **Hazards**

Effects of Overexposure: CAUSE HEADACHE, NAUSEA, IMPAIRMENT OF REACTION TIME AND COORDINATION.

## First Aid

First Aid: INHALATION: MOVE TO FRESH AIR TO IMPROVE BREATHING; SKIN: WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING; EYES: FLUSH WITH WATER FOR AT LEAST 15 MIN. CALL A PHYSICIAN.

## Fire Fighting

Flash Point: 100-150F-(T.O.C)  
Lower Limits: 1.0  
Upper Limits: 7.0  
Extinguishing Media: CO<sub>2</sub>, FOAM, DRY CHEM.  
Fire Fighting Procedures: COOL CLOSED CONTAINERS W/ H<sub>2</sub>O USING FOG NOZZLES.

## Accidental Release

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. STOP LEAK. H<sub>2</sub>O SPRAY COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT, SHOVEL INTO METAL DRUMS; LG SPILL: DIKE W COMMERCIAL ABSORBENT, PUMP INTO COVERED DRUMS.

## Handling

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS & OPEN FLAMES. CLOSE CONTAINERS AFTER EACH USE. DO NOT STORE ABOVE 120F  
Other Precautions: WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR SMOKING; OBSERVE LABEL PRECAUTIONS; CONTAINERS SHOULD BE GROUNDED WHEN POURING; USE NON-SPARKING TOOLS TO REMOVE SPILL; AVOID BREATHING VAPORS.

## Exposure Controls

Respiratory Protection: USE CARTRIDGE-TYPE RESP IAW MFR DIRECTION IF AIR CONTAMENTS UNCONTROLLED  
Ventilation: LOCAL & MECH PROVIDE SUFFICIENT VENT TO KEEP BELOW TLV LEVEL  
Protective Gloves: IMPERVIOUS  
Eye Protection: SAFETY/CHEM GOGGLES  
Other Protective Equipment: USE APPROPRIATE INDUSTRIAL HYGIENE PRACTICES.  
Supplemental Safety and Health  
MSDS FM MFR DATED: 03/01/74; VAP PRESSURE & VAP DENSITY NOTED OF PRINCIPAL SOLVENT.

## Chemical Properties

HCC: F4  
Boiling Pt: B.P. Text: 266-419F  
Vapor Pres: 10  
Vapor Density: 3.7  
Spec Gravity: 0.919  
Evaporation Rate & Reference: SLOWER THAN ETHER  
Solubility in Water: NEGLIGIBLE  
Appearance and Odor: SEMI-VISCOUS CLEAR LIQUID; MILD SOLVENT ODOR  
Percent Volatiles by Volume: 61.0

## Stability

Stability Indicator/Materials to Avoid: YES  
PER MFR NONE REASONABLY FORESEEABLE  
Stability Condition to Avoid: HEAT, IGNITION SOURCES  
Hazardous Decomposition Products: CO, CO<sub>2</sub>, SMOKE

## Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.